



Manufacturing Test reports Pre-Preproduction 2 Radios

Radio Test Results

- 1. Locomotive Test Results (Report 1 of 4)**
- 2. Wayside Test Results (Report 2 of 4)**
- 3. 24 Volt Base Test Results (Report 3 of 4)**
- 4. 48 Volt Base test Results (Report 4 of 4)**



This work was funded in whole or in part by the Federal Railroad Administration, US Department of Transportation under U.S. Government Grant FR-TEC-0003-11-01-00, and is therefore subject to the following license: The Government is granted for itself and others acting on its behalf a paid-up, nonexclusive, irrevocable worldwide license in this work to reproduce, prepare derivative works, distribute copies to the public, and perform publicly and display publicly, by or behalf of the Government. All other rights are reserved by the copyright owner.

By downloading, using, or referring to this document or any of the information contained herein you acknowledge and agree:

Ownership

This document and the information contained herein are the property of Meteorcomm LLC ("MCC"). Except for the limited rights granted under the above license, you obtain no rights in or to the document, its contents, or any related intellectual property all of which are the property of MCC.

Limited Use and Non Disclosure

This document is protected by copyright, trade secret, and other applicable laws.

Disclaimer of Warranty

This document and all information contained within this document or otherwise provided by MCC, and all intellectual property rights within, are provided on a "as is" basis. MCC makes no warranties of any kind and expressly disclaims all warranties, whether express, implied or statutory, including, but not limited to warranties of merchantability, fitness for a particular purpose, title, non-infringement, accuracy, completeness, interference with quiet enjoyment, system integration, or warranties arising from course of dealing, usage, or trade practice.

Assumption of Risk

You are responsible for conducting your own independent assessment of the information contained in this document (including without limitation schematic symbols, footprints and layer definitions) and for confirming its accuracy. You may not rely on the information contained herein and agree to validate all such information using your own technical experts. Accordingly, you agree to assume sole responsibility for your review, use of, or reliance on the information contained in this document. MCC assumes no responsibility for, and you unconditionally and irrevocably release and discharge MCC and its affiliates and their respective officers, directors, and employees ("MCC Parties") from any and all loss, claim, damage or other liability associated with or arising from your use of any of the information contained in this document.

Limitation of Liability & Disclaimer

This document is disseminated under the sponsorship of the Department of Transportation in the interest of information exchange. The United States Government assumes no liability for its contents or use thereof.

In no event shall MCC or the MCC parties be liable for any indirect, incidental, exemplary, special, punitive, or treble or consequential damages or losses, whether such liability is based on contract, warranty, tort (including negligence), product liability, or otherwise, regardless as to whether they have notice as to any such claims.

Any opinions, findings, conclusions, or recommendations expressed in this publication are those of the author(s) and do not necessarily reflect the view of the Federal Railroad Administration and/or U.S. DOT

Trade or manufacturers' names any appear herein solely because they are considered essential to the objective of this report.

Hazardous Uses

None of the information contained in this document may be used in connection with the design, manufacture or use of any equipment or software intended for use in any fail safe applications or any other application where a failure may result in loss of human life or personal injury, property damage, or have a financial impact or in connection with any nuclear facility or activity or shipment or handling of any hazardous, ultra hazardous or similar materials ("Hazardous Uses"). MCC disclaims all liability of every kind for any Hazardous Uses, and you release MCC and the MCC Parties from and shall indemnify MCC and the MCC Parties against any such liability, including, but not limited to, any such liability arising from MCC's negligence.

Copyright and Trademark

Meteorcomm® and JTCnet® are registered trademarks of Meteorcomm LLC., and may not be used without express written permission of Meteorcomm LLC.

Trade or manufactures name may appear herein solely because they are considered essential to the objective of this report. The United States Government does not endorse products or manufacturers.

Document Number: 00002629-A

Manufacturing Test reports Pre- Preproduction 2 Radios

1. Locomotive Radio Manufacturing Test Report
(Report 1 of 4)

UUT Report

| Station ID | Serial Number | Date | Time | Operator | Execution Time | Number of Results | UUT Result |
|------------|---------------|------------------------|-------------|----------|---------------------------|-------------------|------------|
| OXN-WKSDR9 | 63LR000309CA | Monday, March 05, 2012 | 11:55:13 AM | ASupalia | 2613.381170799998 seconds | 1240 | Passed |

Begin Sequence: MainSequence

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|----------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Report Sequence File Version | Done | | | | | |
| Report Text: | 0.0.4.52 | | | | | |
| Initialize | Passed | | | | | |

Begin Sequence: InitializeRadioEthernetCom

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------|---|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Open Port | Passed | | | | | |
| Report Text: | 01/01/00 00:17:08 Booted, Initializing... RAMDISK initialized FLASH Drive C: initialized FLASH Drive D: initialized -- FPGA load success -- -- DSP load success -- 00:17:11.499 System RF Initialization Start 00:17:11.500 Debugger Start Up 00:17:11.509 BootRestore: port:0, mode:0, rev:0, size:0 01/01/00 00:17:11 NO CIM Found 01/01/00 00:17:11 CBUF port 16 ITC PACKET DATA RADIO (c) Copyright 2011 Meteorcomm LLC All Rights Reserved S/W Part Number P63020-A18-00.29.02 ITC SVN r23151 Tue Jan 03 12:27:53 2012 S/W Part Number P63020-D04-00.29.02 DSP SVN r23104 Tue Jan 02 20:18:45 2012 S/W Part Number P63020-F07-00.29.02 FPGA SVN r23090 Wed Dec 28 23:11:05 2011 S/W Part Number P63020-C00 Flexbus CPLD Version 2.7 Tue Nov 22 19:26:37 2011 S/W Part Number P63020-B01 Boot Launcher Rev. 0.22.1 SVN 17525 2011-07-29 H/W Locomotive Board ITC Role: Locomotive Open SSL Copyright (C) 1998 Eric Young (eay@cryptsoft.com) RC2 Provided by BNSF 9/22/2006. RC2 is a trademark of RSA Security Inc. 00:17:11.619 System RF Initialization Complete 00:17:11.721 CIM script failed to run 00:17:11.798 Message No: 00000500:002, 0008 CHARS, 002 SEGMENTS 00:17:11.799 Routing 00000500:002 RMP to: 00000002 00:17:12.853 GPS Antenna State Change - Antenna State: UNKNOWN Antenna Power: UNKNOWN 00:17:13.550 Interface opened on port: Ethernet1 IP:10.10.1.254 00:17:16.097 Interface opened on port: Ethernet2 IP:10.10.2.254 00:17:18.639 Ethernet port 1 Connected 00:17:18.701 Ethernet port 2 Connected 00:17:25.507 Connection Opened:10.10.1.10:64118 00:17:25.577 Connection Opened:10.10.1.10:64118 + | | | | | |
| Disable CIM | Done | | | | | |
| Report Text: | INILOCK,OFF 01/01/00 00:17:28 + | | | | | |
| Unlock Cal | Passed | | | | | |
| Report Text: | CALRAND 30545 + CAL_UNLOCK,30545 Unlocking CAL Parameters OK012 Meteorcomm LLC. All Rights Reserved. DCN 00002629-A 12/17/2012 | | | | | |

| | |
|---|--|
| HOST: 12V PS Temp : PASS : 34.176 HOST: 28V PS Temp : PASS : 34.087 HOST: PA Temp : PASS : 27.893 HOST: Driver Temp : PASS : 27.893 HOST: PA Current : PASS : 0.000 HOST: Driver Current : PASS : 0.000 DSP: CLOCK : PASS DSP: EDMA : PASS DSP: GPIO : PASS DSP: SPI : PASS DSP: MCASP : PASS DSP: PSC : PASS DSP: EXTERNAL CLOCK : PASS DSP: IQ MIXER : PASS DSP: RX ADC : PASS DSP: TX NULL ADC : PASS DSP: DDS : PASS FPGA: MEMORY : PASS | |
| boot loader version 0.22.1 SVN 17525 2011-07-29 reset_count 1 active_index 1 active_source Flash1 active_user USER_BOOT | |
| Inx Pri Stat Fail Lnc Name Notes Last Status ----- 1 1 RDY 1 0 C:A1802902.BIN ACTV Success | |
| TxPower Query | Done |
| Report Text: | Site Assigned Tx Power Level = 46.99 dBm |
| Get PA Temp | Passed 27.893 degrees Celsius |
| | LOG |

End Sequence: InitializeRadioEthernetCom

| Step | Status | Measurement | Units | Limits | | |
|----------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Format and Partition | Passed | | | | | |

Begin Sequence: Format & Flash

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------------|--|--------------|-------|--------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Get Apps Table | Passed | Flash1 | | Flash1 | | IgnoreCase |
| Report Text: | *** BEGIN *** BOOTINFO INFORMATION ***** ----- tag_id 3 length 254 version 0.22.1 SVN 17525 2011-07-29 reset_count 0 active_index 1 active_source Flash1 active_user USER_APP schedule.enable OFF schedule.status BLANK schedule.index 256 schedule.sched 256/00/2255 00:00 *** END *** BOOTINFO INFORMATION ***** Inx Pri Stat Fail Lnc Date Time Size Name Notes Last Status ----- 1 1 RDY 0 0 01/01/2000 12:01 AM 3776504 C:A1802902.BIN ACTV | | | | | |
| Check App Version | Passed | 00.29.02 | | 00.29.02 | | IgnoreCase |
| Check Boot Launcher Version | Passed | 0.22.1 | | 0.22.1 | | IgnoreCase |
| Check CPLD Version | Passed | 2.7 | | 2.7 | | IgnoreCase |
| Check SN | Passed | 63LR000309CA | | 63LR000309CA | | IgnoreCase |
| Check Cust ID | Passed | 00009876 | | 00009876 | | IgnoreCase |
| Check Board Type | Passed | PreProd | | PreProd | | IgnoreCase |
| Report Text: | ITC Role: Locomotive, Board Type: PreProd | | | | | |
| Test SD Card | Passed | | | | | |
| Check SD Write Protect 12/17/2012 | Passed | 00009876 | | 00009876 | | IgnoreCase |

| | | | | | | | |
|-----------|--------|--|--|--|--|--|--|
| Test POST | Passed | | | | | | |
|-----------|--------|--|--|--|--|--|--|

End Sequence: Format & Flash

| Step | Status | Measurement | Units | Limits | | |
|----------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx Tests | Passed | | | | | |

Begin Sequence: RXTTESTS

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| RSSI Cal Diversity | Passed | | | | | |

Begin Sequence: Cal RSSI

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -50 | | | | |
| RSSI Cal | Passed | | -50 | -50.1 | -49.9 | GELE(>= <=) |
| RSSI CAL [Out]: | | -114.6 | | | | |
| Save Cal | Passed | | | | | |
| Report Text: | | CALRAND 31089 + CAL,SAVE,31089 Saving CAL Parameters OK | | | | |

End Sequence: Cal RSSI

| Step | Status | Measurement | Units | Limits | | |
|------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| RSSI Cal Primary | Passed | | | | | |

Begin Sequence: Cal RSSI

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -50 | | | | |
| RSSI Cal | Passed | | -50 | -50.1 | -49.9 | GELE(>= <=) |
| RSSI CAL [Out]: | | -114.6 | | | | |
| Save Cal | Passed | | | | | |
| Report Text: | | CALRAND 7320 + CAL,SAVE,7320 Saving CAL Parameters OK | | | | |

End Sequence: Cal RSSI

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | | 16000 | | | | |

| | | | | |
|--------------------------------|--------|--|--|--|
| Tx Port 217.7125 MHz Full Rate | Passed | | | |
|--------------------------------|--------|--|--|--|

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 217712500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 3.81e-006 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0.001949318 | | | | |
| Statistics.RSSI [Out]: | | -108.5 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 219.9125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -108.1 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 221.8875 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221887500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(>= <=) |
| Get BER | Passed | | | | | |

| | | | | |
|------------------------|--------|-----------|-----------|--------|
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 513 | 495 | GT(>) |
| Duration [In]: | 10 | | | |
| Statistics.PER [Out]: | 0 | | | |
| Statistics.RSSI [Out]: | -106.9 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | 8000 | | | | | |
| Tx Port 217.7125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217712500 | | | | | |
| Amplitude [In]: | -111 | | | | | |
| Rx Max Current Drain | Passed | 0.37 ampere | 0.20 | 0.50 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | | LE(<=) |
| Packets | Passed | 512 | 495 | | | GT(>) |
| Duration [In]: | 20 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -111.6 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219912500 | | | | | |
| Amplitude [In]: | -111 | | | | | |
| Rx Max Current Drain | Passed | 0.37 ampere | 0.20 | 0.50 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | | LE(<=) |
| Packets | Passed | 513 | 495 | | | GT(>) |
| Duration [In]: | 20 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -111 | | | | | |

| Step | Status | Measurement | Units | Limits | |
|--------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Tx Port 221.8875 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|-----------|-------------|-----------|-----------|--------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | 221887500 | | | | |
| Amplitude [In]: | -111 | | | | |
| Rx Max Current Drain | Passed | 0.37 ampere | 0.20 | 0.50 | GELE(> = <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | 495 | | GT(>) |
| Duration [In]: | 20 | | | | |
| Statistics.PER [Out]: | 0 | | | | |
| Statistics.RSSI [Out]: | -109.9 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Configure ESG For Full Rate | Done | | | | |
| Symbol Rate [In]: | 16000 | | | | |
| Rx2 Port 217.7125 MHz Full Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|------------|-------------|-----------|-----------|--------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | 217712500 | | | | |
| Amplitude [In]: | -108 | | | | |
| Rx Max Current Drain | Passed | 0.37 ampere | 0.20 | 0.50 | GELE(> = <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 5.74e-005 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 510 | 495 | | GT(>) |
| Duration [In]: | 10 | | | | |
| Statistics.PER [Out]: | 0.02941176 | | | | |
| Statistics.RSSI [Out]: | -108.1 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Rx2 Port 219.9125 MHz Full Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |

| | | | | | | | | |
|------------------------|-------------|-----------|--------|-----------|------|-------------|--|--|
| Frequency Hz [In]: | 219912500 | | | | | | | |
| Amplitude [In]: | -108 | | | | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(>= <=) | | |
| Get BER | Passed | | | | | | | |
| Measurement: | | | | | | | | |
| BER | Passed | 1.52e-005 | | 1.00e-004 | | LE(<=) | | |
| Packets | Passed | 513 | | 495 | | GT(>) | | |
| Duration [In]: | 10 | | | | | | | |
| Statistics.PER [Out]: | 0.007797271 | | | | | | | |
| Statistics.RSSI [Out]: | -107.7 | | | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port 221.8875 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-------------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 221887500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 1.90e-005 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | | 495 | | GT(>) |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0.007797271 | | | | | |
| Statistics.RSSI [Out]: | -106.6 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | 8000 | | | | | |
| Rx2 Port 217.7125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|-----------------|----------------------|----------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217712500 | | | | | |
| Amplitude [In]: | -111 | | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 7.61e-006 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | | 495 | | GT(>) |
| Duration [In]: | 12/17/2012 | © 2012 | Agteorcomm LLC. | All Rights Reserved. | DCN 00002629-A | |

| | |
|------------------------|-------------|
| Statistics.PER [Out]: | 0.003898635 |
| Statistics.RSSI [Out]: | -111.6 |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219912500 | | | | | |
| Amplitude [In]: | -111 | | | | | |
| Rx Max Current Drain | Passed | 0.37 ampere | 0.20 | 0.50 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | LE(<=) | |
| Packets | Passed | 512 | | 495 | GT(>) | |
| Duration [In]: | 20 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -111 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port 221.8875 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 221887500 | | | | | |
| Amplitude [In]: | -111 | | | | | |
| Rx Max Current Drain | Passed | 0.37 ampere | 0.20 | 0.50 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | LE(<=) | |
| Packets | Passed | 513 | | 495 | GT(>) | |
| Duration [In]: | 20 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -109.9 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | 16000 | | | | | |
| Tx Port High Input Level 217.7625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 217762500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(> = <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -22.2 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port High Input Level 219.9625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219962500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(> = <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -22.2 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port High Input Level 221.9375 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221937500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(> = <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -22.2 | | | | |

| | | | | |
|------------------------|--------|-----|-----|-------|
| Packets | Passed | 513 | 495 | GT(>) |
| Duration [In]: | 10 | | | |
| Statistics.PER [Out]: | 0 | | | |
| Statistics.RSSI [Out]: | -22.2 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port High Input Level 217.7625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|--------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217762500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.37 ampere | 0.20 | 0.50 | GELE(> = <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 513 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -22.2 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port High Input Level 219.9625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|--------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219962500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.37 ampere | 0.20 | 0.50 | GELE(> = <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 511 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -22.2 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port High Input Level 221.9375 MHz | Passed | | | | | |

12/17/2012 12:20:12 AM All Rights Reserved DCM00000500.A

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221937500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | 0.20 | 0.50 | GELE(> = <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 513 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -22.2 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | | 8000 | | | | |
| Tx Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: SimultaneousReceive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -50 | | | | |
| Rx Max Current Drain | Passed | 0.37 | ampere | | | LOG |
| Get BER Channel 1 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 256 | | 0 | | GT(>) |
| Get BER Channel 2 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 257 | | 0 | | GT(>) |
| Get BER Channel 4 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 256 | | 0 | | GT(>) |
| Get BER Channel 5 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 256 | | 0 | | GT(>) |
| Get BER Channel 6 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 256 | | 0 | | GT(>) |
| Get BER Channel 6 | Passed | | | | | |
| Measurement: | | | | | | |
| © 2012 Meteorcomm LLC. All Rights Reserved. DCN 00002629-A | | | | | | |

| | | | | |
|-------------------|--------|-----------|-----------|--------|
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 257 | 0 | GT(>) |
| Get BER Channel 7 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 256 | 0 | GT(>) |
| Get BER Channel 8 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 255 | 0 | GT(>) |
| Get BER Channel 9 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 256 | 0 | GT(>) |

End Sequence: SimultaneousReceive

End Sequence: RXTTESTS

| Step | Status | Measurement | Units | Limits | | |
|------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Bias Check | Passed | | | | | |

Begin Sequence: PA BIAS Setpoint

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|--------------------------|--------|-------------------|-------------|-----------|--------------|
| | | | | Low Limit | High Limit |
| Read PA Bias Current | Passed | 976.5625 | milliampere | 900 | 1100 |
| Voltage Average [Out]: | | 0.390625 | | | GELE(> = <=) |
| Value Average [Out]: | | 0.98 | | | |
| Read Driver Bias Current | Passed | 212.0535714285714 | milliampere | | LOG |
| Voltage Average [Out]: | | 0.4241071428571 | | | |
| Value Average [Out]: | | 0.2128 | | | |

End Sequence: PA BIAS Setpoint

| Step | Status | Measurement | Units | Limits | | |
|-----------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set TxPower Max | Done | | | | | |
| Report Text: | | TXPOWER, +99 Restrict to maximum allowed level Site Assigned Tx Power Level = 46.99 dBm + | | | | |
| PAR | Passed | | | | | |

Begin Sequence: Peak to Average Power Ratio

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|----------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx PAR Current Drain | Passed | 1.547 | ampere | | | LOG |
| Measure PAR | Passed | 3.74 | dB | | | LOG |
| Measurement Data[0] [Out]: | | 43.15604703 | | | | |

12/11/2012 © 2012 MetersControl, LLC. All Rights Reserved. DON 00002029A

End Sequence: Peak to Average Power Ratio

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 74V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.50 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.83 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.80E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.51E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.98 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1254.40 | | | | LOG |
| Reverse Power | Passed | 411.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 74V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.55 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.90 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.83E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.50E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.86 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1332.80 | | | | LOG |
| Reverse Power | Passed | 529.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 74V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.59 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 47.00 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.88E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.50E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.89 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 862.40 | | | | LOG |
| Reverse Power | Passed | 529.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 45V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.35 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.84 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.85E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.51E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.99 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1372.00 | | | | LOG |
| Reverse Power | Passed | 372.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 45V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.43 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.92 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.87E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.51E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.85 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 940.80 | | | | LOG |
| Reverse Power | Passed | 372.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 45V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.50 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 47.01 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.93E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.51E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.90 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1430.80 | | | | LOG |
| Reverse Power | Passed | 529.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 100V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.18 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.83 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.90E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -1.53E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.98 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1332.80 | | | | LOG |
| Reverse Power | Passed | 450.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 100V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.22 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.92 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.92E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -1.52E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.85 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 921.20 | | | | LOG |
| Reverse Power | Passed | 294.00 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 100V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.25 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 47.01 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -7.00E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -1.52E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.88 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1078.00 | | | | LOG |
| Reverse Power | Passed | 470.40 | | | | LOG |

End Sequence: Transmit

12/17/2012 © 2012 Meteorcomm LLC. All Rights Reserved. DCN 00002629-A

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 217.6125MHz 74V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.59 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.94 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -7.02E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -1.53E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.93 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1176.00 | | | | LOG |
| Reverse Power | Passed | 509.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 74V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.54 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.85 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -6.99E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -1.54E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.86 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1195.60 | | | | LOG |
| Reverse Power | Passed | 490.00 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 221.9875MHz 74V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.50 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.77 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -7.04E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -1.56E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 1.00 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1215.20 | | | | LOG |
| Reverse Power | Passed | 333.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| Transmit DQPSK @ 217.6125MHz 45V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.48 | ampere | 1.00 | 4.00 | GELE(> = <=) |
| Tx Nominal Rated Output Power | Passed | 46.94 | dBm PEP | 46.50 | 47.50 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -7.08E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | | -1.54E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.90 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 1019.20 | | | | LOG |
| Reverse Power | Passed | 411.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 45V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.41 | ampere | 1.00 | 4.00 | GELE(> = <=) |
| Tx Nominal Rated Output Power | Passed | 46.86 | dBm PEP | 46.50 | 47.50 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -7.01E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | | -1.54E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.84 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 901.60 | | | | LOG |
| Reverse Power | Passed | 372.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 221.9875MHz 45V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.33 | ampere | 1.00 | 4.00 | GELE(> = <=) |
| Tx Nominal Rated Output Power | Passed | 46.77 | dBm PEP | 46.50 | 47.50 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -7.04E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | | -1.56E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.99 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 901.60 | | | | LOG |
| Reverse Power | Passed | 490.00 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|------------|--------|---------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| 12/17/2012 | 2012 | Telecomin LLC | Al | Units | Less | YTD |
| | | | | Low Limit | High Limit | Comparison Type |

| | |
|-----------------------------------|--------|
| Transmit DQPSK @ 217.6125MHz 100V | Passed |
|-----------------------------------|--------|

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.24 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.94 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -7.12E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.55E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.91 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1313.20 | | | | LOG |
| Reverse Power | Passed | 529.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 100V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.21 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.86 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -7.13E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.57E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.85 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1156.40 | | | | LOG |
| Reverse Power | Passed | 509.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 221.9875MHz 100V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.17 | ampere | 1.00 | 4.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 46.78 | dBm PEP | 46.50 | 47.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -7.13E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.58E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 1.01 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1038.80 | | | | LOG |
| Reverse Power | Passed | 411.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Power Control Range | Passed | | | | | LOG |

Begin Sequence: Power Control Range

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-----------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set Power Level | Done | | | | | |
| Report Text: | | Site Assigned Tx Power Level = 41.74 dBm | | | | |

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 74V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.09 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 41.65 | dBm PEP | 41.25 | 42.25 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -7.08E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | | -1.56E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.84 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 627.20 | | | | LOG |
| Reverse Power | Passed | 431.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 74V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.08 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 41.59 | dBm PEP | 41.25 | 42.25 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -7.09E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | | -1.56E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.86 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 803.60 | | | | LOG |
| Reverse Power | Passed | 372.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 45V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.65 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 41.66 | dBm | 41.25 | 42.25 | GELE(> = <=) |

| | | | | | | |
|-------------------------------|------------|------------|------|------------|-----------|--------------|
| Tx Frequency Accuracy | Passed | -7.12E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | -1.56E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.85 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 901.60 | | | | LOG |
| Reverse Power | Passed | 313.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 45V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 1.65 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 41.59 | dBm PEP | 41.25 | 42.25 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -7.15E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | -1.57E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.85 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 744.80 | | | | LOG |
| Reverse Power | Passed | 294.00 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 100V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 0.85 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 41.66 | dBm PEP | 41.25 | 42.25 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -7.15E-002 | ppm | -2.50E-001 | 2.50E-001 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | -1.57E+001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.84 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 607.60 | | | | LOG |
| Reverse Power | Passed | 372.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 100V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|----------------------|--------|-------------|---------|----------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | All Right | dBm PEP | DCN #0002629-A | | LOG |

| | | | | | |
|-------------------------------|------------|----------------|------------|-----------|-------------|
| Tx Nominal Rated Output Power | Passed | 41.59 dBm PEP | 41.25 | 42.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -7.17E-002 ppm | -2.50E-001 | 2.50E-001 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -1.58E+001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.85 %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 862.40 | | | LOG |
| Reverse Power | Passed | 352.80 | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------|--|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Restore Power Level | Done | | | | | |
| Report Text: | TXPOWER, +5.250000 | | | | | |
| | Site Assigned Tx Power Level = 46.99 dBm | | | | | |

End Sequence: Power Control Range

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR Low Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 43.23 dBm | | | | LOG |
| Lower Adjacent Channel Power | Passed | -70.97 dBc | | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -71.30 dBc | | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR Mid Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 43.10 dBm | | | | LOG |
| Lower Adjacent Channel Power | Passed | -71.70 dBc | | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -72.32 dBc | | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|---------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR High Frequency | Passed | | | | | |

Begin Sequence: ACPR

End Sequence: MainSequence

End UUT Report

Manufacturing Test reports Pre- Preproduction 2 Radios

2. Wayside Manufacturing Test Report (Report 2 of 4)

UUT Report

| Station ID | Serial Number | Date | Time | Operator | Execution Time | Number of Results | UUT Result |
|------------|---------------|--------------------------|------------|----------|----------------------|-------------------|------------|
| OXN-WKSDR9 | 63WR000511CA | Thursday, March 15, 2012 | 8:34:08 AM | ASupalla | 1927.3141935 seconds | 588 | Passed |

Begin Sequence: MainSequence

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|----------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Report Sequence File Version | Done | | | | | |
| Report Text: | 0.0.4.52 | | | | | |
| Initialize | Passed | | | | | |

Begin Sequence: InitializeRadioEthernetCom

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------|---|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Open Port | Passed | | | | | |
| Report Text: | 01/23/00 17:25:45 Booted, Initializing... RAMDISK initialized FLASH Drive C: initialized FLASH Drive D: initialized -- FPGA load success -- -- DSP load success -- RTC Alarm Was Set 17:25:47.053 Debugger Start Up 17:25:47.053 System RF Initialization Start 01/23/00 17:25:47 CBUF port 16 ITC PACKET DATA RADIO (c) Copyright 2011 Meteorcomm LLC All Rights Reserved S/W Part Number P63010-A17-00.29.02 ITC SVN r23151 Tue Jan 03 12:27:53 2012 S/W Part Number P63010-D06-00.29.02 DSP SVN r23104 Tue Jan 02 20:22:23 2012 S/W Part Number P63010-F06-00.29.02 FPGA SVN r23090 Wed Dec 28 23:11:05 2011 S/W Part Number P63010-C00 Flexbus CPLD Version 2.7 Tue Nov 22 19:26:37 2011 S/W Part Number P63010-B01 Boot Launcher Rev. 0.22.1 SVN 17525 2011-07-29 H/W Wayside Board ITC Role: Wayside Open SSL Copyright (C) 1998 Eric Young (eay@cryptsoft.com) RC2 Provided by BNSF 9/22/2006. RC2 is a trademark of RSA Security Inc. 17:25:47.070 System RF Initialization Complete 17:25:47.124 BootRestore: port:0, mode:0, rev:0, size:0 01/23/00 17:25:47 17:25:47.381 SD CIM table file created NO CIM Found 17:25:47.531 CIM script failed to run 17:25:47.611 Message No: 00000500:002, 0008 CHARS, 002 SEGMENTS 17:25:47.612 Routing 00000500:002 RMP to: 00000002 17:25:48.666 GPS Antenna State Change - Antenna State: INIT Antenna Power: ON 17:25:49.317 Interface opened on port: Ethernet1 IP:10.10.1.254 17:25:51.749 Interface opened on port: Ethernet2 IP:10.10.2.254 17:25:54.291 Ethernet port 1 Connected 17:25:54.353 Ethernet port 2 Connected 17:26:03.301 Connection Opened:10.10.1.10:54585 17:26:03.362 Connection Opened:10.10.1.10:54585 + | | | | | |
| Disable CIM | Done | | | | | |
| Report Text: | INILOCK,OFF 01/23/00 17:26:07 + | | | | | |
| Unlock Cal | Passed | | | | | |
| Report Text: | CALRAND 30545 12/17/2012 © 2012 Meteorcomm LLC. All Rights Reserved. DCN 00002629-A CAL,UNLOCK,30545 Unlocking CAL Parameters | | | | | |

| | | | | | |
|------------------------|--|--|--|--|--|
| OK | Passed | Cal Params are UNLOCKED | | | |
| Read Cal | Report Text: | Cal Data Version(1024): 0A.04 XO = 479 IGAIN = 0 QGAIN = 0 DLSLEVEL = 69 PBIAS = 909 TKKEYTO = 0 RSSI_OFF_P = -118.80 RSSI_OFF_D = -100.00 OK | | | |
| Read ipconfig | Report Text: | Ethernet1(+): Enabled:Yes DHCP:OFF NAT:OFF Poll:0ms IP:10.10.1.254 Ethernet2(+): Enabled:Yes DHCP:OFF NAT:OFF Poll:0ms IP:10.10.2.254 Gateway: (Auto) Mask E1: 255.255.255.0 Mask E2: 255.255.255.0 MAC E1: 00-15-23-01-07-0A MAC E2: 00-15-23-01-07-0B EthTxRate: 100 Mbps | | | |
| Set SN and Lock Config | Done | | | | |
| Report Text: | Serial Number Locked | | | | |
| Query Post | Done | | | | |
| Report Text: | ***** Host Post Log ***** | | | | |
| | Board Type: Wayside | | | | |
| | HOST: DDR Address Line Test : PASS HOST: DDR Data Line Test : PASS HOST: SPI : PASS HOST: SDCARD Present : PASS HOST: SDCARD Fall Pin : PASS HOST: SDCARD Write Protect : OFF HOST: SDCARD Access : PASS HOST: I2C Controller : PASS HOST: RTC : PASS HOST: BOOT FLASH (C) : PASS HOST: BOOT FLASH (D) : PASS HOST: DATA FLASH (E) : PASS HOST: SEEPROM STAMP : PASS HOST: CALIBRATION PARAMETERS : PASS HOST: REG PARAMETERS : PASS HOST: ID PARAMETERS : PASS HOST: CHANNEL TABLE : PASS HOST: SITENAME : PASS HOST: DHCP CONTROL : PASS HOST: SERIAL NUMBER : PASS HOST: FPGA LOAD : PASS HOST: DSP LOAD : PASS HOST: DSP RUNNING : PASS HOST: MAC 0 : PASS HOST: MAC 1 : PASS HOST: GPS : PASS HOST: CIM : FAIL HOST: 5v Supply : PASS : 5.037 HOST: 3.3v Supply : PASS : 3.265 HOST: 2.5v Supply : PASS : 2.479 HOST: 1.8v Supply (Host) : PASS : 1.789 HOST: 1.5v Supply : PASS : 1.498 HOST: 1.2v Supply : PASS : 1.194 HOST: ExtV Supply : PASS : 12.834 HOST: 6V Supply : PASS : 5.946 HOST: PA Temp : PASS : 21.341 DSP: CLOCK : PASS DSP: EDMA : PASS DSP: GPIO : PASS DSP: SPI : PASS DSP: MCASP : PASS DSP: PSC : PASS DSP: EXTERNAL CLOCK : PASS DSP: DDS : PASS FPGA: MEMORY : PASS | | | | |
| | boot loader version 0.22.1 SVN 17525 2011-07-29 reset_count 1 active_index 1 active_source Flash1 active_user USER_BOOT | | | | |

| | | | |
|---|--|---------------------------|-----|
| 1 1 RDY 1 0 C:A1702902.bin ACTV Success | | | |
| TxPower Query | Done | | |
| Report Text: | Site Assigned Tx Power Level = 44.00 dBm | | |
| Get PA Temp | Passed | 21.341 degrees Celsius | LOG |

End Sequence: InitializeRadioEthernetCom

| Step | Status | Measurement | Units | Limits | | |
|----------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Format and Partition | Passed | | | | | |

Begin Sequence: Format & Flash
(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------|--|--------------|-------|--------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Get Apps Table | Passed | Flash1 | | Flash1 | | IgnoreCase |
| Report Text: | <pre> ** BEGIN ** BOOTINFO INFORMATION ***** tag_id 3 length 254 version 0.22.1 SVN 17525 2011-07-29 reset_count 0 active_index 1 active_source Flash1 active_user USER_APP schedule.enable OFF schedule.status BLANK schedule.index 256 schedule.sched 256/00/2255 00:00 ** END ** BOOTINFO INFORMATION ***** Inx Pri Stat Fail LncH Date Time Size Name Notes Last Status ----- 1 1 RDY 0 0 01/01/2000 01:42 AM 2351404 C:A1702902.bin ACTV </pre> | | | | | |
| Check App Version | Passed | 00.29.02 | | 00.29.02 | | IgnoreCase |
| Check Boot Launcher Version | Passed | 0.22.1 | | 0.22.1 | | IgnoreCase |
| Check CPLD Version | Passed | 2.7 | | 2.7 | | IgnoreCase |
| Check SN | Passed | 63WR000511CA | | 63WR000511CA | | IgnoreCase |
| Check Cust ID | Passed | 00009876 | | 00009876 | | IgnoreCase |
| Check Board Type | Passed | PreProd | | PreProd | | IgnoreCase |
| Report Text: | ITC Role: Wayside, Board Type: PreProd | | | | | |
| Test SD Card | Passed | | | | | |
| Check SD Write Protect | Passed | OFF | | OFF | | IgnoreCase |
| Test POST | Passed | | | | | |

End Sequence: Format & Flash

| Step | Status | Measurement | Units | Limits | | |
|----------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx Tests | Passed | | | | | |

Begin Sequence: RXTTESTS
(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| RSSI Cal Primary | Passed | | | | | |

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|--|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 219912500 | | | |
| Amplitude [In]: | | -50 | | | |
| RSSI Cal | Passed | -50 | | -50.1 | -49.9 |
| RSSI CAL [Out]: | | -118.7 | | | |
| Save Cal | Passed | | | | |
| Report Text: | | CALRAND 31089 + CAL_SAVE,31089 Saving CAL Parameters OK | | | |

End Sequence: Cal RSSI

| Step | Status | Measurement | Units | Limits | |
|--------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Configure ESG For Full Rate | Done | | | | |
| Symbol Rate [In]: | | 16000 | | | |
| Tx Port 217.7125 Mhz Full Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|--------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 217712500 | | | |
| Amplitude [In]: | | -108 | | | |
| Rx Max Current Drain | Passed | 0.66 | ampere | 0.40 | 1.00 |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | LE(<=) |
| Packets | Passed | 504 | | 495 | GT(>) |
| Duration [In]: | | 10 | | | |
| Statistics.PER [Out]: | | 0 | | | |
| Statistics.RSSI [Out]: | | -107.5 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|--------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Tx Port 219.9125 Mhz Full Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|--------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 219912500 | | | |
| Amplitude [In]: | | -108 | | | |
| Rx Max Current Drain | Passed | 0.66 | ampere | 0.40 | 1.00 |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | LE(<=) |
| Packets | Passed | 505 | | 495 | GT(>) |

| | | | | | | | | | |
|------------------------|--------|--|--|--|--|--|--|--|--|
| | | | | | | | | | |
| Duration [In]: | 10 | | | | | | | | |
| Statistics.PER [Out]: | 0 | | | | | | | | |
| Statistics.RSSI [Out]: | -107.8 | | | | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 221.8875 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-------|-----------|--------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 221887500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.66 ampere | 0.40 | 1.00 | GELE(> = <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 507 | | 495 | | GT(>) |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -108.8 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | 8000 | | | | | |
| Tx Port 217.7125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-------|-----------|--------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217712500 | | | | | |
| Amplitude [In]: | -111 | | | | | |
| Rx Max Current Drain | Passed | 0.66 ampere | 0.40 | 1.00 | GELE(> = <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 505 | | 495 | | GT(>) |
| Duration [In]: | 20 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -110.4 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|--------|-----------|-------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 219912500 | | | |
| Amplitude [In]: | | -111 | | | |
| Rx Max Current Drain | Passed | 0.66 | ampere | 0.40 | 1.00 |
| Get BER | Passed | | | | GELE(>= <=) |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | LE(<=) |
| Packets | Passed | 506 | | 495 | GT(>) |
| Duration [In]: | | 20 | | | |
| Statistics.PER [Out]: | | 0 | | | |
| Statistics.RSSI [Out]: | | -111 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|--------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Tx Port 221.8875 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|--------|-----------|-------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 221887500 | | | |
| Amplitude [In]: | | -111 | | | |
| Rx Max Current Drain | Passed | 0.66 | ampere | 0.40 | 1.00 |
| Get BER | Passed | | | | GELE(>= <=) |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | LE(<=) |
| Packets | Passed | 505 | | 495 | GT(>) |
| Duration [In]: | | 20 | | | |
| Statistics.PER [Out]: | | 0 | | | |
| Statistics.RSSI [Out]: | | -111.8 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Configure ESG For Full Rate | Done | | | | |
| Symbol Rate [In]: | | 16000 | | | |
| Tx Port High Input Level 217.7625 MHz | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 2012000000 | | | |
| Amplitude [In]: | | -7 | | | |

| | | | | | |
|------------------------|--------|-------------|-----------|------|-------------|
| Rx Max Current Drain | Passed | 0.69 ampere | 0.40 | 1.00 | GELE(>= <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 504 | 495 | | GT(>) |
| Duration [In]: | 10 | | | | |
| Statistics.PER [Out]: | 0 | | | | |
| Statistics.RSSI [Out]: | -26.3 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port High Input Level 219.9625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219962500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.69 ampere | 0.40 | 1.00 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 504 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -26.3 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port High Input Level 221.9375 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 221937500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.69 ampere | 0.40 | 1.00 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 504 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -26.4 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | 8000 | | | | | |
| Tx Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: SimultaneousReceive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|--------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219912500 | | | | | |
| Amplitude [In]: | -50 | | | | | |
| Rx Max Current Drain | Passed | 0.663 ampere | | | | LOG |
| Get BER Channel 1 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 253 | | 0 | | GT(>) |
| Get BER Channel 2 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 253 | | 0 | | GT(>) |

End Sequence: SimultaneousReceive

End Sequence: RXTTESTS

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| GPS | Passed | | | | | |

Begin Sequence: GPS

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|---------------------------|---|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| GPS Lock | Passed | | | | | |
| min value [Out]: | 22 | | | | | |
| NMEA Data.GSA.NMEA [Out]: | \$GPGSA,A,3,13,27,20,04,08,25,02,23.0000,2.11,1.04,1.84*05 | | | | | |
| NMEA Data.GGA.NMEA [Out]: | \$GPGGA,010114.00,1949.13354,N,15559.28089,W,1,08,1.04,90.4,M,2.1,M,0.0,0.0 | | | | | |
| GPS Input Level (dBm): | -130 | | | | | |
| GPS DC Source | Passed | 2.81 | | 2.25 | 2.95 | GELE(> = <=) |

End Sequence: GPS

| Step | Status | Measurement | Units | Limits | | |
|-----------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set TxPower Max | Done | | | | | |
| Report Text: | | TXPOWER,+99 Restrict to maximum allowed level Site Assigned Tx Power Level = 44.00 dBm | | | | |
| PAR | Passed | | | | | |

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Measure PAR | Passed | 3.14 | dB | | | LOG |
| Measurement Data[0] [Out]: 40.9390192 | | | | | | |

End Sequence: Peak to Average Power Ratio

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 13.6V | Passed | | | | | |

Begin Sequence: Wayside Transmit
(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 43.6 | dBm PEP | 43.0 | 45.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 0.000 | ppm | -0.250 | 0.250 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: 0.090 | | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 2.09 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 13.6V | Passed | | | | | |

Begin Sequence: Wayside Transmit
(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 44.0 | dBm PEP | 43.0 | 45.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 0.000 | ppm | -0.250 | 0.250 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: 0.104 | | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 2.14 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 13.6V | Passed | | | | | |

Begin Sequence: Wayside Transmit
(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 44.0 | dBm PEP | 43.0 | 45.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -0.000 | ppm | -0.250 | 0.250 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: -0.051 | | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 1.80 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 10.9V 12/17/2012 | Passed | | | | | |
| © 2012 Mettocomm LLC. All Rights Reserved. DON_00002629-A | | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 42.8 | dBm PEP | 41.0 | 46.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -0.000 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | | -0.050 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 3.35 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 10.9V | Passed | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 43.3 | dBm PEP | 41.0 | 46.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 0.000 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | | 0.068 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 3.48 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 10.9V | Passed | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 43.4 | dBm PEP | 41.0 | 46.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -0.001 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | | -0.113 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 3.02 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 15.5V | Passed | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 43.8 | dBm PEP | 41.0 | 46.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -0.001 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | | -0.195 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 1.41 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 15.5V | Passed | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 44.2 | dBm PEP | 41.0 | 46.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 0.000 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | 0.079 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 1.44 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 15.5V | Passed | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 44.2 | dBm PEP | 41.0 | 46.0 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -0.000 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | -0.042 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 1.27 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Power Control Range | Passed | | | | | |

Begin Sequence: Wayside Power Control Range

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-----------------|--|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set Power Level | Done | | | | | |
| Report Text: | TXPOWER,-7.500000 | | | | | |
| | Site Assigned Tx Power Level = 36.50 dBm | | | | | |
| PAR | Passed | | | | | |

Begin Sequence: Peak to Average Power Ratio

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|----------------------------|-------------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Measure PAR | Passed | 4.3 | dB | | | LOG |
| Measurement Data[0] [Out]: | 33.73571805 | | | | | |

End Sequence: Peak to Average Power Ratio

12/17/2012 © 2012 Metgorcomm LLC. All Rights Reserved. DCN 00002629-A

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 13.6V | Passed | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 38.4 | dBm PEP | 30.0 | 39.8 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -0.003 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | -0.695 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.42 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 10.9V | Passed | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 38.0 | dBm PEP | 30.0 | 40.8 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -0.003 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | -0.686 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.41 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|---|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 15.5V | Passed | | | | | |

Begin Sequence: Wayside Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Nominal Rated Output Power | Passed | 38.5 | dBm PEP | 30.0 | 40.8 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -0.003 | ppm | | | LOG |
| Frequency Error (Hz) [Out]: | -0.673 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.40 | %rms | 0.10 | 5.00 | GELE(>= <=) |

End Sequence: Wayside Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------|--|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Restore Power Level | Done | | | | | |
| Report Text: | TXPOWER,+7.500000 Site Assigned Tx Power Level = 44.00 dBm Measured Transmit Power (36.0 dBm) does not match Site Transmit Power (44.0 dBm) + | | | | | |

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR Low Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 40.64 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -80.82 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -80.77 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR Mid Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 40.74 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -79.53 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -79.23 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|---------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR High Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 40.32 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -80.39 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -80.30 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|----------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Sideband Spectrum | Passed | | | | | |

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |

| Step | Status | Measurement | Units | Limits | | |
|-------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Sideband Spectrum | Passed | | | | | |

End Sequence: TX Sideband Spectrum

| Step | Status | Measurement | Units | Limits | | |
|----------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | | | | | |

Begin Sequence: Wayside TX Current Drain

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Current Drain - 217.6125Mhz | Passed | 7.00 | ampere | 5.00 | 10.00 | GELE(>= <=) |
| Tx Current Drain - 219.8125Mhz | Passed | 6.98 | ampere | 5.00 | 10.00 | GELE(>= <=) |
| Tx Current Drain - 221.9875Mhz | Passed | 6.97 | ampere | 5.00 | 10.00 | GELE(>= <=) |

End Sequence: Wayside TX Current Drain

| Step | Status | Measurement | Units | Limits | | |
|---------------|---|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Ping LAN Port | Passed | | | | | |
| LED Test | Passed | | | | | |
| Lock Cal | Passed | | | | | |
| Report Text: | +CALRAND 7320 + CAL_LOCK,7320 Locking CAL Parameters OK | | | | | |
| Read Cal | Passed | | | | | |
| Report Text: | Cal Params are LOCKED Cal Data Version(1024): 0A.04 XO = 479 IGAIN = 0 QGAIN = 0 DDSLEVEL = 69 PBIAS = 909 TXKEYTO = 0 RSSI_OFF_P = -118.70 RSSI_OFF_D = -100.00 OK | | | | | |

End Sequence: MainSequence

End UUT Report

Manufacturing Test reports Pre- Preproduction 2 Radios

3. Base 24V Radio Manufacturing Test Report (Report 3 of 4)

UUT Report

| Station ID | Serial Number | Date | Time | Operator | Execution Time | Number of Results | UUT Result |
|------------|---------------|-----------------------|------------|----------|---------------------------|-------------------|------------|
| OXN-WKSDRM | 63B2000317CA | Monday, June 25, 2012 | 3:07:36 PM | 6812 | 1047.554393599999 seconds | 1408 | Passed |

Begin Sequence: MainSequence

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|----------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Report Sequence File Version | Done | | | | | |
| Report Text: | 0.0.4.66 | | | | | |
| Initialize | Passed | | | | | |

Begin Sequence: InitializeRadioEthernetCom

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------|--|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Open Port | Passed | | | | | |
| Report Text: | 01/12/00 05:17:55 Booted, Initializing... RAMDISK initialized FLASH Drive C: initialized FLASH Drive D: initialized -- FPGA load success -- -- DSP load success -- RTC Alarm Was Set 05:17:58.420 System RF Initialization Start 05:17:58.421 Debugger Start Up 05:17:58.430 BootRestore: port:0, mode:0, rev:0, size:0 01/12/00 05:17:58 NO CIM Found 01/12/00 05:17:58 CBUF port 16 ITC PACKET DATA RADIO (C) Copyright 2011 Meteorcomm LLC All Rights Reserved S/W Part Number P63020-A18-00.29.02 ITC SVN r23151 Tue Jan 03 12:27:53 2012 S/W Part Number P63020-D04-00.29.02 DSP SVN r23104 Tue Jan 02 20:18:45 2012 S/W Part Number P63020-F07-00.29.02 FPGA SVN r23090 Wed Dec 28 23:11:05 2011 S/W Part Number P63020-C00 Flexbus CPLD Version 2.7 Tue Nov 22 19:26:37 2011 S/W Part Number P63020-B01 Boot Launcher Rev. 0.22.1 SVN 17525 2011-07-29 H/W Base Board ITC Role: Base Open SSL Copyright (C) 1998 Eric Young (eay@cryptsoft.com) RC2 Provided by BNSEF 9/22/2006. RC2 is a trademark of RSA Security Inc. 05:17:58.554 System RF Initialization Complete 05:17:58.643 CIM script failed to run 05:17:58.720 Message No: 00000500:002, 0008 CHARS, 002 SEGMENTS 05:17:58.721 Routing 00000500:002 RMP to: 00000002 05:17:59.775 GPS Antenna State Change - Antenna State: UNKNOWN Antenna Power: UNKNOWN 05:18:00.408 Interface opened on port: Ethernet1 IP:10.10.1.254 05:18:02.058 GPS Antenna State Change - Antenna State: INIT Antenna Power: ON 05:18:02.852 Interface opened on port: Ethernet2 IP:10.10.2.254 05:18:05.395 Ethernet port 1 Connected 05:18:05.457 Ethernet port 2 Connected 05:18:12.432 Connection Opened:10.10.1.10:56296 05:18:12.503 Connection Opened:10.10.1.10:56296 + | | | | | |
| Disable CIM | Done | | | | | |
| Report Text: | + INILOCK_OFF 01/12/00 05:18:15 | | | | | |
| Unlock Cal | Passed | | | | | |
| Report Text: | CALRAND 30545 + CAL_UNLOCK_30545 Unlocking CAL Parameters OK | | | | | |
| Read Cal | Passed | | | | | |

| | |
|------------------------|---|
| Report Text: | <p>Cell Params are UNLOCKED</p> <p>Cal Data Version(1024): 0A.04 XO = 306 IDC = 617 QDC = 1470 IGAIN = 561 OGAIN = 561 CBUS_R2 = 0xec CBUS_R5 = 0x20 CBUS_R6 = 0x1e CBUS_R7 = 0x00 CBUS_R8 = 0x00 TXKEYTO = 0 RSSI_OFF_P = -120.60 RSSI_OFF_D = -120.90 TEMP_SP = -30, -22, -14, -6, 2, 10, 18, 26, 34, 42, 50, 58, 66, 74 REQ_SP = 23, 67, 111, 156 PHASE_F1 = 0x18, 0x20, 0x20, 0x28, 0x28, 0x30, 0x30, 0x38, 0x38, 0x38, 0x38, 0x40, 0x40, 0x40, 0x48 PHASE_F2 = 0x28, 0x28, 0x28, 0x28, 0x30, 0x30, 0x38, 0x38, 0x40, 0x40, 0x40, 0x48, 0x48, 0x48, 0x48, 0x50 PHASE_F3 = 0x30, 0x30, 0x38, 0x38, 0x38, 0x38, 0x40, 0x40, 0x48, 0x48, 0x48, 0x48, 0x50, 0x50, 0x58, 0x58, 0x58, 0x58 PHASE_F4 = 0x30, 0x38, 0x38, 0x38, 0x38, 0x38, 0x40, 0x40, 0x48, 0x48, 0x48, 0x48, 0x50, 0x50, 0x58, 0x58 PHASE_F5 = 0x40, 0x40, 0x40, 0x40, 0x48, 0x48, 0x48, 0x48, 0x50, 0x50, 0x50, 0x50, 0x58, 0x58, 0x60, 0x60 OK</p> |
| Read Ipcnfig | Passed |
| Report Text: | <p>Ethemet1(+): Enabled:Yes DHCP:OFF NAT:OFF Poll:0ms IP:10.10.1.254 Ethemet2(+): Enabled:Yes DHCP:OFF NAT:OFF Poll:0ms IP:10.10.2.254 Gateway: (Auto) Mask E1: 255.255.255.0 Mask E2: 255.255.255.0 MAC E1: 00-15-23-01-05-FA MAC E2: 00-15-23-01-05-FB EthTRate: 100 Mbps</p> |
| Set SN and Lock Config | Done |
| Report Text: | Serial Number Locked |
| Query Post | Done |
| Report Text: | <p>***** Host Post Log *****</p> <p>Board Type: Base</p> <p>HOST: DDR Address Line Test : PASS HOST: DDR Data Line Test : PASS HOST: SPI : PASS HOST: SDCARD Present : PASS HOST: SDCARD Fail Pin : PASS HOST: SDCARD Write Protect : OFF HOST: SDCARD Access : PASS HOST: I2C Controller : PASS HOST: I2C Mux : PASS HOST: RTC : PASS HOST: BOOT FLASH (C) : PASS HOST: BOOT FLASH (D) : PASS HOST: DATA FLASH (E) : PASS HOST: EEPROM STAMP : PASS HOST: CALIBRATION PARAMETERS : PASS HOST: REG PARAMETERS : PASS HOST: ID PARAMETERS : PASS HOST: CHANNEL TABLE : PASS HOST: SITEMAME : PASS HOST: DHCP CONTROL : PASS HOST: SERIAL NUMBER : PASS HOST: FPGA LOAD : PASS HOST: DSP LOAD : PASS HOST: DSP RUNNING : PASS HOST: FAN CONTROLLER : PASS HOST: MAC 0 : PASS HOST: MAC 1 : PASS HOST: GPS : PASS HOST: CIM : FAIL HOST: 28v Supply : PASS : 28.772 HOST: 11.5v Supply : PASS : 11.369 HOST: 5v Supply : PASS : 5.017 HOST: 3.3v Supply : PASS : 3.300 HOST: 2.5v Supply : PASS : 2.481 HOST: 1.8v Supply (Host) : PASS : 1.797 HOST: 1.8v Supply (DSP) : PASS : 1.825 HOST: 1.5v Supply : PASS : 1.480 HOST: 1.2v Supply : PASS : 1.196 HOST: EXTV Supply : PASS : 2.391 HOST: 12V PS Temp : PASS : 27.402 HOST: 28V PS Temp : PASS : 27.402 HOST: PA Temp : PASS : 26.457</p> |

| | | | | |
|---|--|--------|-----------------|-----|
| HOST: Driver Temp : PASS : 26.457 HOST: PA Current : PASS : 0.000 HOST: Driver Current : PASS : 0.000 DSP: CLOCK : PASS DSP: EDMA : PASS DSP: GPIO : PASS DSP: SPI : PASS DSP: MCASP : PASS DSP: PSC : PASS DSP: EXTERNAL CLOCK : PASS DSP: IQ MIXER : PASS DSP: RX ADC : PASS DSP: TX NULL ADC : PASS DSP: DDS : PASS FPGA: MEMORY : PASS boot loader: version 0.22.1 SVN 17525 2011-07-29 reset_count 1 active_index 1 active_source Flash1 active_user USER_BOOT Inx Pri Stat Fail Lncn Name Notes Last Status ----- 1 1 RDY 1 0 C:A1802902.BIN ACTV Success | | | | |
| TxPower Query | Done | | | |
| Report Text: | Site Assigned Tx Power Level = 48.75 dBm | | | |
| Get PA Temp | Passed | 26.457 | degrees Celsius | LOG |

End Sequence: InitializeRadioEthernetCom

| Step | Status | Measurement | Units | Limits | | |
|----------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Format and Partition | Passed | | | | | |

Begin Sequence: Format & Flash

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------|---|--------------|-------|--------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Get Apps Table | Passed | Flash1 | | Flash1 | | IgnoreCase |
| Report Text: | <pre> ** BEGIN ** BOOTINFO INFORMATION **** tag_id 3 length 254 version 0.22 1 SVN 17525 2011-07-29 reset_count 0 active_index 1 active_source Flash1 active_user USER_APP schedule.enable OFF schedule.status BLANK schedule.index 256 ** END ** BOOTINFO INFORMATION **** Inx Pri Stat Fail Lncn Date Time Size Name Notes Last Status ----- 1 1 RDY 0 0 01/07/2000 08:20 PM 3776504 C:A1802902.BIN ACTV </pre> | | | | | |
| Check App Version | Passed | 00.29.02 | | 00.29.02 | | IgnoreCase |
| Check Boot Launcher Version | Passed | 0.22.1 | | 0.22.1 | | IgnoreCase |
| Check CPLD Version | Passed | 2.7 | | 2.7 | | IgnoreCase |
| Check SN | Passed | 6382000317CA | | 6382000317CA | | IgnoreCase |
| Check Cust ID | Passed | 00009876 | | 00009876 | | IgnoreCase |
| Check Board Type | Passed | PreProd | | PreProd | | IgnoreCase |
| Report Text: | ITC Role: Base, Board Type: PreProd | | | | | |
| Test SD Card | Passed | | | | | |
| Check SD Write Protect | Passed | OFF | | OFF | | IgnoreCase |
| Test POST | Passed | | | | | |

End Sequence: Format & Flash

| | | | | Limits |
|--|--|--|--|--------|
| | | | | |

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|----------|--------|-------------|-------|-----------|------------|-----------------|
| Rx Tests | Passed | | | | | |

Begin Sequence: RXTTESTS

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| RSSI Cal Diversity | Passed | | | | | |

Begin Sequence: Cal RSSI

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -50 | | | | |
| RSSI Cal | Passed | | -50 | -50.1 | -49.9 | GELE(>= <=) |
| RSSI CAL [Out]: | | -120.9 | | | | |
| Save Cal | Passed | | | | | |
| Report Text: | | CALRAND 31.089 + CAL_SAVE,31.089 Saving CAL Parameters OK | | | | |

End Sequence: Cal RSSI

| Step | Status | Measurement | Units | Limits | | |
|------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| RSSI Cal Primary | Passed | | | | | |

Begin Sequence: Cal RSSI

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -50 | | | | |
| RSSI Cal | Passed | | -50 | -50.1 | -49.9 | GELE(>= <=) |
| RSSI CAL [Out]: | | -120.8 | | | | |
| Save Cal | Passed | | | | | |
| Report Text: | | CALRAND 7320 + CAL_SAVE,7320 Saving CAL Parameters OK | | | | |

End Sequence: Cal RSSI

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | | 16000 | | | | |
| Tx Port 217.7125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| | | | | | |
|-------------------------------|-----------|-------------|-----------|------|-------------|
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | 217712500 | | | | |
| Amplitude [In]: | -108 | | | | |
| Rx Max Current Drain | Passed | 0.94 ampere | 0.60 | 1.20 | GELE(>= <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 507 | 495 | | GT(>) |
| Duration [In]: | 10 | | | | |
| Statistics.PER [Out]: | 0 | | | | |
| Statistics.RSSI [Out]: | -109.2 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 219.9125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

| (C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq) | | | | | | |
|--|-----------|-------------|-----------|-----------|-------------|-----------------|
| Step | Status | Measurement | Units | Limits | | |
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219912500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.94 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -107.9 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 221.8875 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

| (C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq) | | | | | | |
|--|-----------|-------------|-----------|-----------|-------------|-----------------|
| Step | Status | Measurement | Units | Limits | | |
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 221887500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.94 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 506 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -108.1 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | 8000 | | | | | |
| Tx Port 217.7125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217712500 | | | | | |
| Amplitude [In]: | -11.1 | | | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 | GELE(> = <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | | 495 | | GT(>) |
| Duration [In]: | 20 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -112.1 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219912500 | | | | | |
| Amplitude [In]: | -11.1 | | | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 | GELE(> = <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 507 | | 495 | | GT(>) |
| Duration [In]: | 20 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -111.2 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 221.8875 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| | | | | |
|-------------------------------|-----------|-------------|-----------|------------------|
| Set ESG Frequency & Amplitude | Done | | | |
| Frequency Hz [In]: | 221887500 | | | |
| Amplitude [In]: | -111 | | | |
| Rx Max Current Drain | Passed | 0.94 ampere | 0.60 | 1.20 GELE(>= <=) |
| Get BER | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 507 | 495 | GT(>) |
| Duration [In]: | 20 | | | |
| Statistics.PER [Out]: | 0 | | | |
| Statistics.RSSI [Out]: | -111.2 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | 16000 | | | | | |
| Rx1 Port 217.7125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217712500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.94 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 1.16e-005 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0.00591716 | | | | | |
| Statistics.RSSI [Out]: | -108.7 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port 219.9125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219912500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.94 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |

| | |
|------------------------|--------|
| Statistics.PER [Out]: | 0 |
| Statistics.RSSI [Out]: | -107.9 |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port 221.8875 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221.887500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 | GELE(> = <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 3.86e-006 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0.001976285 | | | | |
| Statistics.RSSI [Out]: | | -107.9 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | | 8000 | | | | |
| Rx1 Port 217.7125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 217712500 | | | | |
| Amplitude [In]: | | -111 | | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 | GELE(> = <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | | 495 | | GT(>) |
| Duration [In]: | | 20 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -111.8 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -111 | | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | | 495 | | GT(>) |
| Duration [In]: | | 20 | | | | |
| Statistics:PER [Out]: | | 0 | | | | |
| Statistics:RSSI [Out]: | | -110.9 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port 221.8875 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221867500 | | | | |
| Amplitude [In]: | | -111 | | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 3.85e-006 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 507 | | 495 | | GT(>) |
| Duration [In]: | | 20 | | | | |
| Statistics:PER [Out]: | | 0.001972387 | | | | |
| Statistics:RSSI [Out]: | | -110.9 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | | 16000 | | | | |
| Rx2 Port 217.7125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 217712500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |

| | | | | |
|------------------------|--------|-----------|-----------|--------|
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 507 | 495 | GT(>) |
| Duration [In]: | 10 | | | |
| Statistics.PER [Out]: | 0 | | | |
| Statistics.RSSI [Out]: | -110 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port 219.9125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 21991.2500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | 0.94 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -108 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port 221.8875 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221887500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | 0.94 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 506 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -108.4 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|-----------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | 8000 | | | | | |

| | | | | | |
|---------------------------------|--------|--|--|--|--|
| Rx2 Port 217.7125 MHz Half Rate | Passed | | | | |
|---------------------------------|--------|--|--|--|--|

Begin Sequence: Receive
(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|--------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 217712500 | | | |
| Amplitude [In]: | | -111 | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | LE(<=) |
| Packets | Passed | 505 | | 495 | GT(>) |
| Duration [In]: | | 20 | | | |
| Statistics.PER [Out]: | | 0 | | | |
| Statistics.RSSI [Out]: | | -112.9 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Rx2 Port 219.9125 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive
(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|--------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 219912500 | | | |
| Amplitude [In]: | | -111 | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | LE(<=) |
| Packets | Passed | 507 | | 495 | GT(>) |
| Duration [In]: | | 20 | | | |
| Statistics.PER [Out]: | | 0 | | | |
| Statistics.RSSI [Out]: | | -111 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Rx2 Port 221.8875 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive
(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|--------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 221887500 | | | |
| Amplitude [In]: | | -111 | | | |
| Rx Max Current Drain | Passed | 0.94 | ampere | 0.60 | 1.20 |
| Get BER | Passed | | | | |

| | | | |
|------------------------|--------|-----------|------------------|
| Measurement: | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 LE(<=) |
| Packets | Passed | 507 | 495 GT(>) |
| Duration [In]: | 20 | | |
| Statistics.PER [Out]: | 0 | | |
| Statistics.RSSI [Out]: | -111.6 | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | 16000 | | | | | |
| Tx Port High Input Level 217.7625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217762500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.97 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 506 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -28.2 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port High Input Level 219.9625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219962500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.97 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -28.2 | | | | | |

End Sequence: Receive

| Limits | | |
|--------|--|--|
| | | |

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| Tx Port High Input Level 221.9375 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|-------------------------------|--------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221937500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.97 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 503 | 495 | | GT(>) | |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -28.2 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | |
| Rx1 Port High Input Level 217.7625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|-------------------------------|--------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 217762500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.97 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -28.2 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | |
| Rx1 Port High Input Level 219.9625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|-------------------------------|--------|-------------|-------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219962500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.97 ampere | 0.60 | 1.20 | GELE(>= <=) | |

| | | | | | |
|------------------------|--------|-----------|-----------|--|--------|
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | 495 | | GT(>) |
| Duration [In]: | 10 | | | | |
| Statistics.PER [Out]: | 0 | | | | |
| Statistics.RSSI [Out]: | -28.2 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port High Input Level 221.9375 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 221937500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.97 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 506 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -28.2 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port High Input Level 217.7625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217762500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.96 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -28.3 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| | | | | | |
|--|--------|--|--|--|--|
| Rx2 Port High Input Level 219.9625 MHz | Passed | | | | |
|--|--------|--|--|--|--|

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|-------------------------------|--------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219962500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.97 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -28.3 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | |
| Rx2 Port High Input Level 221.9375 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|-------------------------------|--------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221937500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.97 ampere | 0.60 | 1.20 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 506 | 495 | | GT(>) | |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -28.3 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | |
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | | 8000 | | | | |
| Tx Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: SimultaneousReceive

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|-------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -50 | | | | |

| | | | | |
|----------------------|--------|--------------|-----------|--------|
| Rx Max Current Drain | Passed | 0.952 ampere | | LOG |
| Get BER Channel 1 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 254 | 0 | GT(>) |
| Get BER Channel 2 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 253 | 0 | GT(>) |
| Get BER Channel 4 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 253 | 0 | GT(>) |
| Get BER Channel 5 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 253 | 0 | GT(>) |
| Get BER Channel 6 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 253 | 0 | GT(>) |
| Get BER Channel 7 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 253 | 0 | GT(>) |
| Get BER Channel 8 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 254 | 0 | GT(>) |
| Get BER Channel 9 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 253 | 0 | GT(>) |

End Sequence: SimultaneousReceive

End Sequence: RXTESTS

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| GPS | Passed | | | | | |

Begin Sequence: GPS

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|---------------------------|--|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| GPS Lock | Passed | | | | | |
| min value [Out]: | 19 | | | | | |
| NMEA Data.GSA.NMEA [Out]: | \$GPGSA,A,3,08,23,20,02,04,27,13,25,,,,,2,1,1,1.05,1.84*04 | | | | | |
| NMEA Data.GGA.NMEA [Out]: | \$GPGGA,010100.00,1949.13300,N,15559.28027,W,1.08,1.05,88.9,M,2.1,M,0.4E | | | | | |

| | | | | | | | | | |
|------------------------|--------|------|--|------|------|--------------|--|--|--|
| GPS Input Level (dbm): | -1.30 | | | | | | | | |
| GPS DC Source | Passed | 2.82 | | 2.25 | 2.95 | GELE(> = <=) | | | |

End Sequence: GPS

| Step | Status | Measurement | Units | Limits | | |
|------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Bias Check | Passed | | | | | |

Begin Sequence: PA BIAS Setpoint

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------------------|--------|-------------|---------------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Read PA Bias Current | Passed | 2626.953125 | milliamperere | 2475 | 3025 | GELE(> = <=) |
| Voltage Average [Out]: | | 1.05078125 | | | | |
| Value Average [Out]: | | 2.6362 | | | | |
| Read Driver Bias Current | Passed | 244.140625 | milliamperere | | | LOG |
| Voltage Average [Out]: | | 0.48828125 | | | | |
| Value Average [Out]: | | 0.245 | | | | |

End Sequence: PA BIAS Setpoint

| Step | Status | Measurement | Units | Limits | | |
|-----------------|--|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set TxPower Max | Done | | | | | |
| Report Text: | TXPOWER, +99 Restrict to maximum allowed level Site Assigned Tx Power Level = 48.75 dbm + | | | | | |
| PAR | Passed | | | | | |

Begin Sequence: Peak to Average Power Ratio

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|----------------------------|-------------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx PAR Current Drain | Passed | 7.085 | ampere | | | LOG |
| Measure PAR | Passed | 3.75 | dB | | | LOG |
| Measurement Data[0] [Out]: | 45.14672037 | | | | | |

End Sequence: Peak to Average Power Ratio

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 24V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 6.94 | ampere | 4.00 | 11.00 | GELE(> = <=) |
| Tx Nominal Rated Output Power | Passed | 48.90 | dBm PEP | 48.25 | 49.25 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | 8.02E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | 1.78E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.93 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 1372.00 | | | | LOG |
| Reverse Power | Passed | 274.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 24V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 7.12 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.97 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.29E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.82E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.97 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1293.60 | | | | LOG |
| Reverse Power | Passed | 352.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 24V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 7.27 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 49.03 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 7.83E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.70E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.91 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 960.40 | | | | LOG |
| Reverse Power | Passed | 274.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 21V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 8.04 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.91 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.02E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.78E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.93 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 999.60 | | | | LOG |
| Reverse Power | Passed | 274.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|-----------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ | Passed | | | | | |

219.8125MHz 21V

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 8.23 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.98 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.33E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.83E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.96 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1195.60 | | | | LOG |
| Reverse Power | Passed | 352.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 21V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 8.41 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 49.02 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 7.79E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.70E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.89 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1136.80 | | | | LOG |
| Reverse Power | Passed | 333.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 27V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 6.15 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.92 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 7.98E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.77E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.92 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 921.20 | | | | LOG |
| Reverse Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 27V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 6.29 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.99 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.31E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.83E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.97 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1038.80 | | | | LOG |
| Reverse Power | Passed | 352.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 27V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 6.41 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 49.02 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 7.85E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.71E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.90 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1215.20 | | | | LOG |
| Reverse Power | Passed | 352.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 217.6125MHz 24V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 7.21 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.96 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 7.86E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.71E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.90 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1176.00 | | | | LOG |
| Reverse Power | Passed | 313.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 24V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CatAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| | | | | | | |
|-------------------------------|-----------|-----------|---------|------------|-----------|-------------|
| Tx Max Current Drain | Passed | 7.07 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.92 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.30E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.83E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.98 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1058.40 | | | | LOG |
| Reverse Power | Passed | 313.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 211.9875MHz 24V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 6.92 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.86 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.04E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.78E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.92 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 882.00 | | | | LOG |
| Reverse Power | Passed | 274.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 217.6125MHz 21V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 8.36 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.96 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 7.84E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.71E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.90 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1313.20 | | | | LOG |
| Reverse Power | Passed | 450.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 21V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 8.18 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.94 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.32E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |

| 1.83E+000 | | | | | | |
|-------------------------------|--------|--------|------|------|------|-------------|
| Frequency Error (Hz) [Out]: | Passed | 0.99 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Modulation Accuracy - EVM-AVG | Passed | 921.20 | | | | LOG |
| Forward Power | Passed | 333.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 21.9875MHz 21V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 7.97 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.86 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.03E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| 1.78E+000 | | | | | | |
| Frequency Error (Hz) [Out]: | Passed | 0.93 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Modulation Accuracy - EVM-AVG | Passed | 1234.80 | | | | LOG |
| Forward Power | Passed | 274.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 217.6125MHz 27V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 6.37 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.96 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 7.87E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| 1.71E+000 | | | | | | |
| Frequency Error (Hz) [Out]: | Passed | 0.90 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Modulation Accuracy - EVM-AVG | Passed | 1117.20 | | | | LOG |
| Forward Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 27V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 6.23 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.93 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.31E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| 1.83E+000 | | | | | | |
| Frequency Error (Hz) [Out]: | Passed | 0.97 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Modulation Accuracy - EVM-AVG | Passed | 921.20 | | | | LOG |
| Forward Power | Passed | | | | | |

| | | | | |
|---------------|--------|--------|--|-----|
| Reverse Power | Passed | 333.20 | | LOG |
|---------------|--------|--------|--|-----|

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 221.9875MHz 27V | Passed | | | | | |

Begin Sequence: Transmit
(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 6.10 | ampere | 4.00 | 11.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.85 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.06E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | 1.79E+000 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.93 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1234.80 | | | | LOG |
| Reverse Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Power Control Range | Passed | | | | | |

Begin Sequence: Power Control Range
(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-----------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set Power Level | Done | | | | | |
| Report Text: | | Site Assigned Tx Power Level = 40.00 dBm Measured Transmit Power (49.4 dBm) does not match Site Transmit Power (40.0 dBm) | | | | |

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 24V | Passed | | | | | |

Begin Sequence: Transmit
(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 5.03 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.23 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.34E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | 1.83E+000 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.94 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 627.20 | | | | LOG |
| Reverse Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 24V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 5.03 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.18 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.38E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.84E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.94 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 666.40 | | | | LOG |
| Reverse Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 21V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 5.78 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.22 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.37E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.84E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.94 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 705.60 | | | | LOG |
| Reverse Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 21V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 5.77 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.16 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.35E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.84E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.95 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 627.20 | | | | LOG |
| Reverse Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 27V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 4.49 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.25 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.45E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.86E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.94 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 686.00 | | | | LOG |
| Reverse Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 27V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 4.47 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.14 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | 8.45E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | 1.86E+000 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.94 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 646.80 | | | | LOG |
| Reverse Power | Passed | 254.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------|--|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Restore Power Level | Done | | | | | |
| Report Text: | TXPOWER,+8.750000 | | | | | |
| | Site Assigned Tx Power Level = 48.75 dBm | | | | | |

End Sequence: Power Control Range

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR Low Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 45.20 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -71.54 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -73.28 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR Mid Frequency | Passed | | | | | |

| | | | | | | | |
|--|--|--|--|--|--|--|--|
| | | | | | | | |
|--|--|--|--|--|--|--|--|

Begin Sequence: ACPR

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 45.11 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -72.24 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -73.51 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|---------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR High Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 45.12 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -72.67 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -73.35 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|----------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| TX Sideband Spectrum | Passed | | | | | |

Begin Sequence: TX Sideband Spectrum

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Sideband Spectrum | Passed | | | | | |

| Step | Status | Measurement | Units | Limits | | |
|-------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Sideband Spectrum | Passed | | | | | |

End Sequence: TX Sideband Spectrum

| Step | Status | Measurement | Units | Limits | | |
|---------------|------------------------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Ping LAN Port | Passed | | | | | |
| LED Test | Passed | | | | | |
| Fan Test | Passed | | | | | |
| Lock Cal | Passed | | | | | |
| Report Text | CALRAND | | | | | |
| | 15125 | | | | | |
| | + CAL_LOCK,15125 | | | | | |
| | Locking CAL Parameters | | | | | |
| | OK | | | | | |

| Read Cal | Passed |
|--------------|--|
| Report Text: | <p>Cal Params are LOCKED</p> <p>Cal Data Version(1024): 0A.04</p> <p>XO = 306</p> <p>IDC = 617</p> <p>QDC = 1470</p> <p>IGAIN = 561</p> <p>QGAIN = 561</p> <p>CBUS_R2 = 0xec</p> <p>CBUS_R5 = 0x20</p> <p>CBUS_R6 = 0x1e</p> <p>CBUS_R7 = 0x00</p> <p>CBUS_R8 = 0x00</p> <p>TXKEYTO = 0</p> <p>RSSI_OFF_P = -120.80</p> <p>RSSI_OFF_D = -120.90</p> <p>TEMP_SP = -30, -22, -14, -6, 2, 10, 18, 26, 34, 42, 50, 58, 66, 74</p> <p>FREQ_SP = 23, 67, 111, 156</p> <p>PHASE_F1 = 0x18, 0x20, 0x20, 0x20, 0x2S, 0x2B, 0x30, 0x30, 0x3B, 0x3B, 0x3B, 0x3B, 0x40, 0x40, 0x40, 0x40, 0x40, 0x48</p> <p>PHASE_F2 = 0x2S, 0x2B, 0x2B, 0x30, 0x30, 0x3B, 0x3B, 0x40, 0x40, 0x4B, 0x4B, 0x4B, 0x50, 0x50, 0x58</p> <p>PHASE_F3 = 0x30, 0x30, 0x3B, 0x3B, 0x3B, 0x3B, 0x40, 0x40, 0x4B, 0x4B, 0x4B, 0x50, 0x50, 0x5B, 0x5B, 0x58</p> <p>PHASE_F4 = 0x30, 0x3B, 0x3B, 0x3B, 0x3B, 0x3B, 0x40, 0x40, 0x4B, 0x4B, 0x4B, 0x50, 0x50, 0x5B, 0x5B, 0x58</p> <p>PHASE_F5 = 0x40, 0x40, 0x40, 0x40, 0x4B, 0x4B, 0x4B, 0x4B, 0x4B, 0x50, 0x50, 0x5B, 0x5B, 0x58, 0x58, 0x60</p> <p>OK</p> |

End Sequence: MainSequence

End UUT Report

Manufacturing Test reports Pre- Preproduction 2 Radios

4. Base 48V Radio Manufacturing Test Report (Report 4 of 4)

UUT Report

| Station ID | Serial Number | Date | Time | Operator | Execution Time | Number of Results | UUT Result |
|------------|---------------|---------------------------|------------|----------|----------------------|-------------------|------------|
| OXN-WKSDRM | 63B4000234CA | Wednesday, April 18, 2012 | 5:06:59 PM | DHanson | 1111.6902049 seconds | 1368 | Passed |

Begin Sequence: MainSequence

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Report Sequence File Version | Done | | | | | |
| Report Text: | | 0.0.4.52 | | | | |
| Initialize | Passed | | | | | |

Begin Sequence: InitializeRadioEthernetCom

(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------|--------|---|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Open Port | Passed | | | | | |
| Report Text: | | 01/03/00 04:25:11 Booted, Initializing... RANDISK initialized FLASH Drive C: initialized FLASH Drive D: initialized -- FPGA load success -- -- DSP load success -- 04:25:14.410 System RF Initialization Start 04:25:14.411 New Boot Launcher was Loaded 04:25:14.420 BootRestore: port:0, mode:0, rev:0, size:0 01/03/00 04:25:14 NO CIM Found 04:25:14.533 System RF Initialization Complete 01/03/00 04:25:14 CBUF port 16 ITC PACKET DATA RADIO (C) Copyright 2011 Meteorcomm LLC All Rights Reserved S/W Part Number P63020-A18-00.29.02 ITC SVN r23151 Tue Jan 03 12:27:53 2012 S/W Part Number P63020-D04-00.29.02 DSP SVN r23104 Tue Jan 02 20:18:45 2012 S/W Part Number P63020-F07-00.29.02 FPGA SVN r23090 Wed Dec 28 23:11:05 2011 S/W Part Number P63020-C00 Flexbus CPLD Version 2.7 Tue Nov 22 19:26:37 2011 S/W Part Number P63020-B01 Boot Launcher Rev. 0.22.1 SVN 17525 2011-07-29 H/W Base Beard ITC Role: Base Open SSL Copyright (C) 1998 Eric Young (eay@cryptsoft.com) RC2 Provided by BNSF 9/22/2006. RC2 is a trademark of RSA Security Inc. 04:25:14.631 CIM script failed to run 04:25:14.709 Message No: 00000500:002, 0008 CHARS, 002 SEGMENTS 04:25:14.710 Routing 00000500:002 RMP to: 00000002 04:25:15.764 GPS Antenna State Change - Antenna State: UNKNOWN Antenna Power: UNKNOWN 04:25:16.426 Interface opened on port: Ethernet1 IP:10.10.1.254 04:25:18.041 GPS Antenna State Change - Antenna State: INIT Antenna Power: ON 04:25:18.887 Interface opened on port: Ethernet2 IP:10.10.2.254 04:25:21.429 Ethernet port 1 Connected 04:25:21.491 Ethernet port 2 Connected 04:25:28.421 Connection Opened:10.10.1.10:54404 04:25:28.492 Connection Opened:10.10.1.10:54404 + | | | | |
| Disable CIM | Done | | | | | |
| Report Text: | | + INLOCK, OFF 01/03/00 04:25:31 | | | | |
| Unlock Cal | Passed | | | | | |
| Report Text: | | CALRAND 30545 + CALUNLOCK,30545 Unlocking CAL Parameters OK | | | | |
| Read Cal | Passed | | | | | |

Report Text:

```

Cal Params are UNLOCKED
Cal Data Version(1024): 0A.04
XO = 278
IDC = 591
QDC = 223
LGAIN = 566
QGAIN = 566
CBUS_R2 = 0xsec
CBUS_R5 = 0x20
CBUS_R6 = 0x1e
CBUS_R7 = 0x00
CBUS_R8 = 0x00
TXKEYTO = 0
RSSI_OFF_P = -100.00
RSSI_OFF_D = -100.00
TEMP_SP = -30, -22, -14, -6, 2, 10, 18, 26, 34, 42, 50, 58, 66, 74
FREQ_SP = 23, 67, 111, 156
PHASE_F1 = 0x18, 0x20, 0x20, 0x28, 0x28, 0x30, 0x30, 0x30, 0x38, 0x38, 0x40, 0x40,
0x40, 0x40, 0x40, 0x40, 0x48
PHASE_F2 = 0x28, 0x28, 0x28, 0x28, 0x30, 0x30, 0x38, 0x38, 0x40, 0x40, 0x40, 0x40,
0x48, 0x48, 0x48, 0x50, 0x50
PHASE_F3 = 0x30, 0x30, 0x30, 0x38, 0x38, 0x38, 0x40, 0x40, 0x40, 0x48, 0x48, 0x48,
0x50, 0x50, 0x58, 0x58, 0x58
PHASE_F4 = 0x38, 0x40, 0x40, 0x40, 0x40, 0x48, 0x48, 0x48, 0x50, 0x50, 0x50,
0x58, 0x58, 0x60, 0x60, 0x60
PHASE_F5 = 0x40, 0x40, 0x40, 0x40, 0x48, 0x48, 0x48, 0x48, 0x50, 0x50, 0x50, 0x50,
0x58, 0x58, 0x58, 0x60, 0x60
OK
    
```

Read ipconfig

| | | | | |
|--------|--|--|--|--|
| Passed | | | | |
|--------|--|--|--|--|

Report Text:

```

Ethernet1(+): Enabled:Yes DHCP:OFF NAT:OFF Poll:0ms IP:10.10.1.254
Ethernet2(+): Enabled:Yes DHCP:OFF NAT:OFF Poll:0ms IP:10.10.2.254
Gateway: (Auto)
Mask E1: 255.255.255.0
Mask E2: 255.255.255.0
MAC E1: 00-15-23-01-05-A6
MAC E2: 00-15-23-01-05-A7
EthTxRate: 100 Mibps
    
```

Query Post

| | | | | |
|------|--|--|--|--|
| Done | | | | |
|------|--|--|--|--|

Report Text:

```

***** Host Post Log *****
Board Type: Base
HOST: DDR Address Line Test : PASS
HOST: DDR Data Line Test : PASS
HOST: SPT : PASS
HOST: SDCARD Present : PASS
HOST: SDCARD Fail Pin : PASS
HOST: SDCARD Write Protect : OFF
HOST: SDCARD Access : PASS
HOST: I2C Controller : PASS
HOST: I2C Flux : PASS
HOST: RTC : PASS
HOST: BOOT FLASH (C) : PASS
HOST: BOOT FLASH (D) : PASS
HOST: DATA FLASH (E) : PASS
HOST: SEEPROM4 STAMP : PASS
HOST: CALIBRATION PARAMETERS : PASS
HOST: REG PARAMETERS : PASS
HOST: ID PARAMETERS : PASS
HOST: CHANNEL TABLE : PASS
HOST: SITEMAME : PASS
HOST: DHICP CONTROL : PASS
HOST: SERIAL NUMBER : FAIL
HOST: FPGA LOAD : PASS
HOST: DSP LOAD : PASS
HOST: DSP RUNNING : PASS
HOST: FAN CONTROLLER : PASS
HOST: MAC 0 : PASS
HOST: MAC 1 : PASS
HOST: GPS : PASS
HOST: CIM : FAIL
HOST: 28v Supply : PASS : 28.754
HOST: 1.5v Supply : PASS : 11.428
HOST: 5v Supply : PASS : 5.012
HOST: 3.3v Supply : PASS : 3.288
HOST: 2.5v Supply : PASS : 2.469
HOST: 1.8v Supply (Host) : PASS : 1.801
HOST: 1.8v Supply (DSP) : PASS : 1.819
HOST: 1.5v Supply : PASS : 1.477
HOST: 1.2v Supply : PASS : 1.191
HOST: Extv Supply : PASS : 2.402
HOST: 12v PS Temp : PASS : 27.580
HOST: 28v PS Temp : PASS : 27.491
HOST: PA Temp : PASS : 26.457
HOST: Driver Temp : PASS : 25.021
HOST: PA Current : PASS : 0.000
HOST: Driver Current : PASS : 0.000
DSP: CLOCK : PASS
DSP: EDMA : PASS
DSP: GPIO : PASS
    
```

| | | | |
|--|--|------------------------------|-----|
| DSP: SPI : PASS DSP: MCASP : PASS DSP: PSC : PASS DSP: EXTERNAL_CLOCK : PASS DSP: IO MIXER : PASS DSP: RX ADC : PASS DSP: TX NULL ADC : PASS DSP: DQS : PASS FPGA: MEMORY : PASS boot loader version 0.22.1 SVN 17525 2011-07-29 reset_count 1 active_index 1 active_source Flash1 active_user USER_BOOT ----- Inx Pri Stat Fail Lnc Name Notes Last Status ----- 1 1 RDY 1 0 C:A1802902.BIN ACTV Success | | | |
| TxPower Query | Done | | |
| Report Text: | Site Assigned Tx Power Level = 48.75 dbm | | |
| Get PA Temp | Passed | 26.457 degrees Celsius | LOG |

End Sequence: InitializeRadioEthernetCom

| Step | Status | Measurement | Units | Limits | | |
|----------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Format and Partition | Passed | | | | | |

Begin Sequence: Format & Flash

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-----------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Test POST | Passed | | | | | |

End Sequence: Format & Flash

| Step | Status | Measurement | Units | Limits | | |
|----------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx Tests | Passed | | | | | |

Begin Sequence: RXTTESTS

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| RSSI Cal Diversity | Passed | | | | | |

Begin Sequence: Cal RSSI

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | -50 | | | | | |
| RSSI Cal | Passed | -50 | | -50.1 | -49.9 | GELE(>= <=) |
| RSSI CAL [Out]: | -115.1 | | | | | |
| Save Cal | Passed | | | | | |
| Report Text: | CALRAND 31089 + CAL_SAVE_31089 Saving CAL Parameters OK | | | | | |

End Sequence: Cal RSSI

| Limits | | | |
|--------|--|--|--|
| | | | |

| Step | Measurement | Units | Low Limit | High Limit | Comparison Type |
|------------------|-------------|-------|-----------|------------|-----------------|
| RSSI Cal Primary | Passed | | | | |

Begin Sequence: Cal RSSI

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|--|-------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 21991.2500 | | | | |
| Amplitude [In]: | | -50 | | | | |
| RSSI Cal | Passed | | -50 | -49.9 | GELE(>= <=) | |
| RSSI CAL [Out]: | | -114.3 | | | | |
| Save Cal | Passed | | | | | |
| Report Text: | | CALRAND 7320 + CAL.SAVE.7320 Saving CAL Parameters OK | | | | |

End Sequence: Cal RSSI

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | | 16000 | | | | |
| Tx Port 21.7125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-------------|-----------|------------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 21771.2500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | | 0.50 ampere | 0.20 | 0.60 GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 5.40e-005 | | 1.00e-004 | LE(<=) | |
| Packets | Passed | 506 | | 495 | GT(>) | |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0.0256917 | | | | |
| Statistics.RSSI [Out]: | | -109.6 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port 219.9125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-------------|-----------|------------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 21991.2500 | | | | |
| Amplitude [In]: | | -108 | | | | |
| Rx Max Current Drain | Passed | | 0.50 ampere | 0.20 | 0.60 GELE(>= <=) | |

| | | | | | |
|------------------------|-------------|-----------|-----------|--|--------|
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 1.16e-005 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | 495 | | GT(>) |
| Duration [In]: | 10 | | | | |
| Statistics.PER [Out]: | 0.005928854 | | | | |
| Statistics.RSSI [Out]: | -108.7 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|--------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Tx Port 221.8875 MHz Full Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|-----------|-------------|-----------|-----------|--------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | 221887500 | | | | |
| Amplitude [In]: | -108 | | | | |
| Rx Max Current Drain | Passed | 0.50 ampere | 0.20 | 0.60 | GELE(> = <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 5.40e-005 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | 495 | | GT(>) |
| Duration [In]: | 10 | | | | |
| Statistics.PER [Out]: | 0.0256917 | | | | |
| Statistics.RSSI [Out]: | -109.6 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|--------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Configure ESG For Half Rate | Done | | | | |
| Symbol Rate [In]: | 8000 | | | | |
| Tx Port 217.7125 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|-----------|-------------|-----------|-----------|--------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | 217712500 | | | | |
| Amplitude [In]: | -111 | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(> = <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 507 | 495 | | GT(>) |
| Duration [In]: | 20 | | | | |
| Statistics.PER [Out]: | 0 | | | | |
| Statistics.RSSI [Out]: | -112.7 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| Tx Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -111 | | | | |
| Rx Max Current Drain | Passed | 0.50 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | | 20 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -112 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| Tx Port 221.8875 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221887500 | | | | |
| Amplitude [In]: | | -111 | | | | |
| Rx Max Current Drain | Passed | 0.50 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 505 | 495 | | GT(>) | |
| Duration [In]: | | 20 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -112.7 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | | 16000 | | | | |
| Rx1 Port 217.7125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |

| | | | | | |
|------------------------|------------|-------------|-----------|------|-------------|
| Frequency Hz [In]: | 217712500 | | | | |
| Amplitude [In]: | -108 | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(>= <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 3.47e-005 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | 495 | | GT(>) |
| Duration [In]: | 10 | | | | |
| Statistics.PER [Out]: | 0.01762178 | | | | |
| Statistics.RSSI [Out]: | -109.1 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port: 219.9125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219912500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 3.08e-005 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0.01577909 | | | | | |
| Statistics.RSSI [Out]: | -108.2 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port: 221.8875 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 221887500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 9.25e-005 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0.04142012 | | | | | |
| Statistics.RSSI [Out]: | -109.1 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Configure ESG For Half Rate | Done | | | | |
| Symbol Rate [In]: | 8000 | | | | |
| Rx1 Port 217.7125 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|-------------|-------------|--------|-----------|-------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | 217712500 | | | | |
| Amplitude [In]: | -111 | | | | |
| Rx Max Current Drain | Passed | 0.49 | ampere | 0.20 | 0.60 |
| Get BER | Passed | | | | GELE(>= <=) |
| Measurement: | | | | | |
| BER | Passed | 3.87e-006 | | 1.00e-004 | LE(<=) |
| Packets | Passed | 505 | | 495 | GT(>) |
| Duration [In]: | 20 | | | | |
| Statistics.PER [Out]: | 0.001980198 | | | | |
| Statistics.RSSI [Out]: | -112 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Rx1 Port 219.9125 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|-------------|-------------|--------|-----------|-------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | 219912500 | | | | |
| Amplitude [In]: | -111 | | | | |
| Rx Max Current Drain | Passed | 0.49 | ampere | 0.20 | 0.60 |
| Get BER | Passed | | | | GELE(>= <=) |
| Measurement: | | | | | |
| BER | Passed | 3.85e-006 | | 1.00e-004 | LE(<=) |
| Packets | Passed | 507 | | 495 | GT(>) |
| Duration [In]: | 20 | | | | |
| Statistics.PER [Out]: | 0.001972387 | | | | |
| Statistics.RSSI [Out]: | -111.3 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Rx1 Port 221.8875 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |

| | | | | | | | | | |
|------------------------|-------------|-------------|-----------|------|-------------|--|--|--|--|
| Frequency Hz [In]: | 221887500 | | | | | | | | |
| Amplitude [In]: | -111 | | | | | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(>= <=) | | | | |
| Get BER | Passed | | | | | | | | |
| Measurement: | | | | | | | | | |
| BER | Passed | 7.70e-006 | 1.00e-004 | | LE(<=) | | | | |
| Packets | Passed | 507 | 495 | | GT(>) | | | | |
| Duration [In]: | 20 | | | | | | | | |
| Statistics.PER [Out]: | 0.003944773 | | | | | | | | |
| Statistics.RSSI [Out]: | -112.7 | | | | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | 16000 | | | | | |
| Rx2 Port 21.7125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-------------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217712500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 3.85e-006 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0.001972387 | | | | | |
| Statistics.RSSI [Out]: | -109 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port 219.9125 MHz Full Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 219912500 | | | | | |
| Amplitude [In]: | -108 | | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -107.8 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Rx2 Port 221.8875 MHz Full Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|-----------|-----------|--------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 221887500 | | | |
| Amplitude [In]: | | -108 | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(> = <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | 495 | | GT(>) |
| Duration [In]: | | 10 | | | |
| Statistics.PER [Out]: | | 0 | | | |
| Statistics.RSSI [Out]: | | -109 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Configure ESG For Half Rate | Done | | | | |
| Symbol Rate [In]: | | 8000 | | | |
| Rx2 Port 217.7125 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|-------------------------------|--------|-------------|-----------|-----------|--------------|
| | | | | Low Limit | High Limit |
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | | 217712500 | | | |
| Amplitude [In]: | | -111 | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(> = <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | 495 | | GT(>) |
| Duration [In]: | | 20 | | | |
| Statistics.PER [Out]: | | 0 | | | |
| Statistics.RSSI [Out]: | | -112.1 | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | |
|---------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Rx2 Port 219.9125 MHz Half Rate | Passed | | | | |

Begin Sequence: Receive

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| | | | | | |

| | | | | | |
|-------------------------------|-------------|-------------|-----------|------|-------------|
| Set ESG Frequency & Amplitude | Done | | | | |
| Frequency Hz [In]: | 21,991,2500 | | | | |
| Amplitude [In]: | -111 | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(>= <=) |
| Get BER | Passed | | | | |
| Measurement: | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | 495 | | GT(>) |
| Duration [In]: | 20 | | | | |
| Statistics.PER [Out]: | 0 | | | | |
| Statistics.RSSI [Out]: | -111 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port 221.8875 MHz Half Rate | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 221887500 | | | | | |
| Amplitude [In]: | -111 | | | | | |
| Rx Max Current Drain | Passed | 0.49 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 506 | 495 | | GT(>) | |
| Duration [In]: | 20 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -112.1 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Configure ESG For Full Rate | Done | | | | | |
| Symbol Rate [In]: | 16000 | | | | | |
| Tx Port High Input Level 217.7625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|-----------|-------------|-----------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | 217762500 | | | | | |
| Amplitude [In]: | -7 | | | | | |
| Rx Max Current Drain | Passed | 0.51 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 506 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |

| | |
|------------------------|-------|
| Statistics:PER [Out]: | 0 |
| Statistics:RSSI [Out]: | -21.9 |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port High Input Level 219.9625 MHz | Passed | | | | | |

Begin Sequence: Receive
(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219962500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.51 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics:PER [Out]: | | 0 | | | | |
| Statistics:RSSI [Out]: | | -21.9 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Port High Input Level 221.9375 MHz | Passed | | | | | |

Begin Sequence: Receive
(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-------|-----------|-------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 221937500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.51 ampere | 0.20 | 0.60 | GELE(>= <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics:PER [Out]: | | 0 | | | | |
| Statistics:RSSI [Out]: | | -21.9 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port High Input Level 217.7625 MHz | Passed | | | | | |

Begin Sequence: Receive
(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| Step | Status | Measurement | Units | Limit | High Limit | Comparison Type |
|-------------------------------|--------|-------------|-----------|-------|--------------|-----------------|
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 21.7762500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.51 ampere | 0.20 | 0.60 | GELE(> = <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 506 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -21.9 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port High Input Level 219.9625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-----------|-----------|--------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 21.9962500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.51 ampere | 0.20 | 0.60 | GELE(> = <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |
| Statistics.RSSI [Out]: | -21.9 | | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx1 Port High Input Level 221.9375 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|-----------|-----------|--------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 22.1937500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.50 ampere | 0.20 | 0.60 | GELE(> = <=) | |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | LE(<=) | |
| Packets | Passed | 507 | 495 | | GT(>) | |
| Duration [In]: | 10 | | | | | |
| Statistics.PER [Out]: | 0 | | | | | |

Statistics.RSSI [Out]: -21.9

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port High Input Level 217.7625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 217762500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.51 | ampere | 0.20 | 0.60 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 506 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -22.7 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port High Input Level 219.9625 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|--------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219962500 | | | | |
| Amplitude [In]: | | -7 | | | | |
| Rx Max Current Drain | Passed | 0.51 | ampere | 0.20 | 0.60 | GELE(>= <=) |
| Get BER | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | | 1.00e-004 | | LE(<=) |
| Packets | Passed | 504 | | 495 | | GT(>) |
| Duration [In]: | | 10 | | | | |
| Statistics.PER [Out]: | | 0 | | | | |
| Statistics.RSSI [Out]: | | -22.7 | | | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Rx2 Port High Input Level 221.9375 MHz | Passed | | | | | |

Begin Sequence: Receive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| Step | Status | Measurement | Units | Limit |
|-------------------------------|--------|-------------|-----------|------------------|
| Set ESG Frequency & Amplitude | Done | | | |
| Frequency Hz [In]: | | 221937500 | | |
| Amplitude [In]: | | -7 | | |
| Rx Max Current Drain | Passed | 0.51 ampere | 0.20 | 0.60 GELE(>= <=) |
| Get BER | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 507 | 495 | GT(>) |
| Duration [In]: | | 10 | | |
| Statistics:PER [Out]: | | 0 | | |
| Statistics:RSSI [Out]: | | -22.7 | | |

End Sequence: Receive

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|--------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| Configure ESG For Half Rate | Done | | | | | |
| Symbol Rate [In]: | | 8000 | | | | |
| Tx Port 219.9125 MHz Half Rate | Passed | | | | | |

Begin Sequence: SimultaneousReceive

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | Comparison Type |
|-------------------------------|--------|--------------|-----------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | |
| Set ESG Frequency & Amplitude | Done | | | | | |
| Frequency Hz [In]: | | 219912500 | | | | |
| Amplitude [In]: | | -50 | | | | |
| Rx Max Current Drain | Passed | 0.497 ampere | | | | LOG |
| Get BER Channel 1 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | | LE(<=) |
| Packets | Passed | 254 | 0 | | | GT(>) |
| Get BER Channel 2 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | | LE(<=) |
| Packets | Passed | 253 | 0 | | | GT(>) |
| Get BER Channel 4 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | | LE(<=) |
| Packets | Passed | 253 | 0 | | | GT(>) |
| Get BER Channel 5 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | | LE(<=) |
| Packets | Passed | 253 | 0 | | | GT(>) |
| Get BER Channel 6 | Passed | | | | | |
| Measurement: | | | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | | | LE(<=) |
| Packets | Passed | 254 | 0 | | | GT(>) |
| Get BER Channel 7 | Passed | | | | | |
| Measurement: | | | | | | |

| | | | | |
|-------------------|--------|-----------|-----------|--------|
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 253 | 0 | GT(>) |
| Get BER Channel 8 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 254 | 0 | GT(>) |
| Get BER Channel 9 | Passed | | | |
| Measurement: | | | | |
| BER | Passed | 0.00e+000 | 1.00e-004 | LE(<=) |
| Packets | Passed | 253 | 0 | GT(>) |

End Sequence: SimultaneousReceive

End Sequence: RXTESTS

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| GPS | Passed | | | | | |

Begin Sequence: GPS

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|---------------------------|--------|---|-------|-----------|--------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| GPS Lock | Passed | | | | | |
| min value [Out]: | | 21 | | | | |
| NMEA Data.GSA.NMEA [Out]: | | \$GPGSA,A,3,27,23,04,20,08,25,13,,,,,,,,,3.41,1.36,3.13*0E | | | | |
| NMEA Data.GGA.NMEA [Out]: | | \$GPGGA,01.0054.00,1949.13269 N,15559.28050 W,1.07,1.36,88.7,M,2.1,M,,*41 | | | | |
| GPS Input Level (dBm): | | -130 | | | | |
| GPS DC Source | Passed | 2.81 | 2.25 | 2.95 | GELE(> = <=) | |

End Sequence: GPS

| Step | Status | Measurement | Units | Limits | | |
|------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Bias Check | Passed | | | | | |

Begin Sequence: PA BIAS Setpoint

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--------------------------|--------|-------------------|-------------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Read PA Bias Current | Passed | 2714.84375 | milliampere | 2475 | 3025 | GELE(> = <=) |
| Voltage Average [Out]: | | 1.0859375 | | | | |
| Value Average [Out]: | | 2.7244 | | | | |
| Read Driver Bias Current | Passed | 228.3960459183674 | milliampere | | | LOG |
| Voltage Average [Out]: | | 0.4567920918367 | | | | |
| Value Average [Out]: | | 0.2292 | | | | |

End Sequence: PA BIAS Setpoint

| Step | Status | Measurement | Units | Limits | | |
|-----------------|--------|---|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Set TxPower Max | Done | | | | | |
| Report Text: | | TXPOWER,+99 Restrict to maximum allowed level Site Assigned Tx Power Level = 48.75 dbm + | | | | |
| PAR | Passed | | | | | |

Begin Sequence: Peak to Average Power Ratio

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | |
|--|--------|-------------|--------|-----------|------------|
| | | | | Low Limit | High Limit |
| Tx PAR Current Drain | Passed | 3.307 | ampere | | LOG |
| Measure PAR | Passed | 3.72 | dB | | LOG |
| Measurement Data[0] [Out]: 45.07671032 | | | | | |

End Sequence: Peak to Average Power Ratio

| Step | Status | Measurement | Units | Limits | |
|---------------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Transmit DQPSK_HALF @ 221.9875MHz 48V | Passed | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.29 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.83 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.02E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: -6.70E-001 | | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1097.60 | | | | LOG |
| Reverse Power | Passed | 352.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | |
|---------------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Transmit DQPSK_HALF @ 219.8125MHz 48V | Passed | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|--|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.32 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.86 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -2.69E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: -5.91E-001 | | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.76 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 764.40 | | | | LOG |
| Reverse Power | Passed | 431.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | |
|---------------------------------------|--------|-------------|-------|-----------|------------|
| | | | | Low Limit | High Limit |
| Transmit DQPSK_HALF @ 217.6125MHz 48V | Passed | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.35 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.87 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |

| | | | | | | |
|-------------------------------|------------|------------|------|------------|-----------|--------------|
| Tx Frequency Accuracy | Passed | -3.24E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | -7.04E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 1058.40 | | | | LOG |
| Reverse Power | Passed | 470.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 42V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.72 | ampere | 2.00 | 6.00 | GELE(> = <=) |
| Tx Nominal Rated Output Power | Passed | 48.85 | dBm PEP | 48.25 | 49.25 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -3.15E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | -6.98E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 1352.40 | | | | LOG |
| Reverse Power | Passed | 313.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 42V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.76 | ampere | 2.00 | 6.00 | GELE(> = <=) |
| Tx Nominal Rated Output Power | Passed | 48.87 | dBm PEP | 48.25 | 49.25 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -2.93E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | -6.43E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.76 | %rms | 0.10 | 2.00 | GELE(> = <=) |
| Forward Power | Passed | 999.60 | | | | LOG |
| Reverse Power | Passed | 392.00 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 42V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.79 | ampere | 2.00 | 6.00 | GELE(> = <=) |
| Tx Nominal Rated Output Power | Passed | 48.87 | dBm PEP | 48.25 | 49.25 | GELE(> = <=) |
| Tx Frequency Accuracy | Passed | -3.37E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(> = <=) |
| Frequency Error (Hz) [Out]: | -7.33E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(> = <=) |

| | | | | | |
|---------------|--------|---------|--|--|-----|
| Forward Power | Passed | 1254.40 | | | LOG |
| Reverse Power | Passed | 548.80 | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 221.9875MHz 54V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.96 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.85 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.16E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -7.02E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.74 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 960.40 | | | | LOG |
| Reverse Power | Passed | 333.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 54V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.98 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.87 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -2.84E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -6.25E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.76 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 980.00 | | | | LOG |
| Reverse Power | Passed | 431.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 217.6125MHz 54V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.01 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.86 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.40E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -7.41E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1117.20 | | | | LOG |
| Reverse Power | Passed | 568.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 217.6125MHz 48V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.33 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.81 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.57E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -7.78E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.78 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1234.80 | | | | LOG |
| Reverse Power | Passed | 548.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 48V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.30 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.82 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -2.97E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -6.52E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.76 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 901.60 | | | | LOG |
| Reverse Power | Passed | 392.00 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 221.9875MHz 48V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.27 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.81 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.28E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -7.28E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1058.40 | | | | LOG |
| Reverse Power | Passed | 352.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| | | | | | |
|----------------------------------|--------|--|--|--|--|
| Transmit DQPSK @ 217.6125MHz 42V | Passed | | | | |
|----------------------------------|--------|--|--|--|--|

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.77 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.83 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.38E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -7.36E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.76 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1234.80 | | | | LOG |
| Reverse Power | Passed | 568.40 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 42V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.73 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.84 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.04E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -6.68E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.77 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1176.00 | | | | LOG |
| Reverse Power | Passed | 431.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 221.9875MHz 42V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 3.69 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.81 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.36E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -7.46E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1234.80 | | | | LOG |
| Reverse Power | Passed | 333.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 217.6125MHz 54V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.99 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.83 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.62E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -7.88E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.76 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 1117.20 | | | | LOG |
| Reverse Power | Passed | 509.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 54V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.97 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.84 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.13E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -6.88E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 940.80 | | | | LOG |
| Reverse Power | Passed | 392.00 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 221.9875MHz 54V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|------------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.94 | ampere | 2.00 | 6.00 | GELE(>= <=) |
| Tx Nominal Rated Output Power | Passed | 48.82 | dBm PEP | 48.25 | 49.25 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.51E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -7.80E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.77 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 960.40 | | | | LOG |
| Reverse Power | Passed | 352.80 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Power Control Range | Passed | | | | | |

Begin Sequence: Power Control Range

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| | | | |
|-----------------|--|--|--|
| Set Power Level | Done | | |
| Report Text: | Site Assigned Tx Power Level = 40.00 dBm | | |

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 48V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.46 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.15 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.14E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -6.90E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.73 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 705.60 | | | | LOG |
| Reverse Power | Passed | 333.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 48V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.46 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.10 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.15E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -6.92E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.73 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 627.20 | | | | LOG |
| Reverse Power | Passed | 313.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 42V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|--------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.77 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.17 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.16E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | | -6.95E-001 | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.72 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 744.80 | | | | LOG |
| Reverse Power | Passed | 333.20 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 42V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.77 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.10 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.21E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -7.06E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.75 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 646.80 | | | | LOG |
| Reverse Power | Passed | 313.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|---------------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK_HALF @ 219.8125MHz 54V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.24 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.16 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.20E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -7.04E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.73 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 666.40 | | | | LOG |
| Reverse Power | Passed | 313.60 | | | | LOG |

End Sequence: Transmit

| Step | Status | Measurement | Units | Limits | | |
|----------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Transmit DQPSK @ 219.8125MHz 54V | Passed | | | | | |

Begin Sequence: Transmit

(C:\Program Files\CalAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------------------|------------|-------------|---------|------------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Tx Max Current Drain | Passed | 2.24 | ampere | | | LOG |
| Tx Nominal Rated Output Power | Passed | 40.10 | dBm PEP | 39.50 | 40.50 | GELE(>= <=) |
| Tx Frequency Accuracy | Passed | -3.26E-003 | ppm | -2.50E-002 | 2.50E-002 | GELE(>= <=) |
| Frequency Error (Hz) [Out]: | -7.17E-001 | | | | | |
| Modulation Accuracy - EVM-AVG | Passed | 0.74 | %rms | 0.10 | 2.00 | GELE(>= <=) |
| Forward Power | Passed | 725.20 | | | | LOG |
| Reverse Power | Passed | 313.60 | | | | LOG |

End Sequence: Transmit

| | | | | Limits | | |
|--|--|--|--|--------|--|--|
| | | | | | | |

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|---------------------|--|-------------|-------|-----------|------------|-----------------|
| Restore Power Level | Done | | | | | |
| Report Text: | TXPOWER,+8.750000 | | | | | |
| | Site Assigned Tx Power Level = 48.75 dBm | | | | | |

End Sequence: Power Control Range

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR Low Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 45.15 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -72.27 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -71.49 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|--------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR Mid Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 45.11 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -72.82 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -71.69 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|---------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR High Frequency | Passed | | | | | |

Begin Sequence: ACPR

(C:\Program Files\CaiAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|------------------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| ACPR | Passed | | | | | |
| Measurement: | | | | | | |
| Reference Carrier Power | Passed | 45.08 | dBm | | | LOG |
| Lower Adjacent Channel Power | Passed | -72.45 | dBc | -70.00 | | LE(<=) |
| Upper Adjacent Channel Power | Passed | -71.57 | dBc | -70.00 | | LE(<=) |

End Sequence: ACPR

| Step | Status | Measurement | Units | Limits | | |
|------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| | | | | | | |

| Step | Status | Measurement | Units | Low Limit | High Limit | Comparison Type |
|----------------------|--------|-------------|-------|-----------|------------|-----------------|
| Tx Sideband Spectrum | Passed | | | | | |

Begin Sequence: TX Sideband Spectrum
(C:\Program Files\CaliAmp Test Systems\MCC Unit Level Test\MCC\MCC - Unit Test.seq)

| Step | Status | Measurement | Units | Limits | | |
|-------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Sideband Spectrum | Passed | | | | | |

| Step | Status | Measurement | Units | Limits | | |
|-------------------|--------|-------------|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Sideband Spectrum | Passed | | | | | |

End Sequence: TX Sideband Spectrum

| Step | Status | Measurement | Units | Limits | | |
|---------------|--------|--|-------|-----------|------------|-----------------|
| | | | | Low Limit | High Limit | Comparison Type |
| Ping LAN Port | Passed | | | | | |
| LED Test | Passed | | | | | |
| Fan Test | Passed | | | | | |
| Lock Cal | Passed | | | | | |
| Report Text: | | CALRAND 15125 + CAL,LOCK,15125 Locking CAL Parameters OK | | | | |
| Read Cal | Passed | | | | | |
| Report Text: | | Cal Params are LOCKED Cal Data Version(1024): 0A.04 XO = 278 IDC = 591 QDC = 223 IGAIN = 566 QGAIN = 566 CBUS_R2 = 0xec CBUS_R5 = 0x20 CBUS_R6 = 0x1e CBUS_R7 = 0x00 CBUS_R8 = 0x00 TXKEYTO = 0 RSSI_OFF_P = -114.30 RSSI_OFF_D = -115.10 TEMP_SP = -30, -22, -14, -6, 2, 10, 18, 26, 34, 42, 50, 58, 66, 74 FREQ_SP = 23, 67, 111, 156 PHASE_F1 = 0x18, 0x20, 0x20, 0x28, 0x28, 0x28, 0x30, 0x30, 0x38, 0x38, 0x38, 0x40, 0x40, 0x40, 0x40, 0x48 PHASE_F2 = 0x28, 0x28, 0x28, 0x30, 0x30, 0x38, 0x38, 0x40, 0x40, 0x40, 0x48, 0x48, 0x48, 0x50, 0x50 PHASE_F3 = 0x30, 0x30, 0x38, 0x38, 0x38, 0x38, 0x40, 0x40, 0x48, 0x48, 0x48, 0x48, 0x50, 0x50, 0x58, 0x58 PHASE_F4 = 0x38, 0x40, 0x40, 0x40, 0x40, 0x48, 0x48, 0x48, 0x48, 0x50, 0x50, 0x58, 0x58, 0x60, 0x60 PHASE_F5 = 0x40, 0x40, 0x40, 0x48, 0x48, 0x48, 0x48, 0x48, 0x50, 0x50, 0x58, 0x58, 0x60, 0x60 OK | | | | |

End Sequence: MainSequence

End UUT Report